



NOTES:

- CONCRETE TO BE 28 DAY COMPRESSIVE STRENGTH TO 4000 PSI.
- NO. 4 REBAR ($\phi 1/2"$) GRADE 60 STEEL PER ASTM A615; CONNECTED WITH TIE WIRE.
- REBAR TO BE 2.5" FROM FACE OF CONCRETE.
- REBAR SPACING 12" GRID, 4" SPACING AROUND ACCESS OPENINGS.
- ALL PENETRATIONS TO BE SLEEVED OR HAVE SLIP CONNECTIONS. MINIMUM 36" FROM TOP OF SLAB TO TOP OF TANK.
- EXTEND COMPACTED BACKFILL A MINIMUM 3 FT. BEYOND ALL SIDES OF TANK.

TANK MODELS
GMC/OMC 4000
GMC/OMC 5000
GMC/OMC 6000
GMC/OMC 7000

WATERTIGHT SEAL WITH SIKAFLEX CAULK

SET 1" GAP BETWEEN CAST IRON FRAME (SUSPENDED IN SLAB) AND COLLAR

TITLE:		REV	DATE	DRAWN
H2O TRAFFIC LOADING SLAB FOR DUAL 92 IN. DIA. TANKS		1	OCTOBER 7, 2010	L. SIMKINS
PROJECT:		2		
WO:		3		
✓ CONFIGURATION:		4		
		5		
		6		
		7		
		8		
		9		
		10		
DRAWN BY: L. SIMKINS		SCALE: 1:10		
DRAWN DATE: OCTOBER 1, 2008		DO NOT SCALE DRAWING		

greenturtle[®]
 US 877 428 8187 CAN 877 966 9444
 www.greenturtletech.com

SIZE	DWG. NO.	REV.
A	DOUBLE SLAB 92 IN TANKS	1
SCALE: 1:10		SHEET 1 OF 1