

Z5320-PED

20" x 23" ADA Lavatory with Half Pedestal

Z5320-PED Series

- 20" x 23" [508mm x 584mm]
- · Vitreous china
- Faucet holes for single, 4", 8", or 12" centers
- · Available with side soap hole drilling
- Designed for convenient access by wheelchairs
- · Wall hung ADA lavatory for use with concealed arm carrier systems
- Vitreous china half pedestal
- · Front overflow
- Waste: 1-1/4" O.D.
- Depth: 3-1/2"
- Shipping Weight: 41 lbs.

Engineering Specification

- ☐ **Z5321-PED** 20" x 23" vitreous china wall hung ADA lavatory with single faucet hole and half pedestal. Provided with holes for concealed arm carrier systems.
- □ **Z5324-PED** 20" x 23" vitreous china wall hung ADA lavatory with 4" center faucet holes and half pedestal. Provided with holes for concealed arm carrier systems.
- □ **Z5328-PED** 20" x 23" vitreous china wall hung ADA lavatory with 8" center faucet holes and half pedestal. Provided with holes for concealed arm carrier systems.
- □ **Z5329-PED** 20" x 23" vitreous china wall hung ADA lavatory with 12" center faucet holes and half pedestal. Provided with holes for concealed arm carrier systems.



Z5320-PED 20" x 23" ADA lavatory with half pedestal shown with Z6920-CP4 gooseneck sensor faucet (sold separately).

Recommended Trim

- ☐ **Z8743-PC** Grid Strainer
- ☐ **Z8700** Series P-Trap
- ☐ **Z8800** Series Stop with Flexible Supplies
- Z8946-1-NT ADA Trap, Stop, and **Supply Protectors**

Optional Trim

- **Z8746-PC** ADA Grid Strainer
- ☐ **Z8946-3-NT** ADA Trap, Stop, and Supply Protectors for Offset Grid Strainers

This Space is for Architectural/Engineering Approval



Fixtures meet ASME A112.19.2 and CSA B45 standard



Meets the American Disabilities Guidelines and ANSI A117.1 requirements when lavatory is installed 34" [864mm] from finished floor.

See Zurn One Systems for suggested packages.