

# *Z5320*

# 20" x 23" ADA Lavatory

# Z5320 Series

- 20" x 23" [508mm x 584mm]
- · Vitreous china
- Faucet holes for single, 4", 8", or 12" centers
- · Available side soap hole drilling
- Designed for convenient access by wheelchairs
- · Wall hung ADA lavatory for use with concealed arm carrier systems
- · Front overflow
- Waste: 1-1/4" O.D.
- Depth: 3-1/2"
- Shipping Weight: 34 lbs.

# Engineering Specification

- $\square$  **Z5321** 20" x 23" with single faucet hole. Vitreous china, wall hung lavatory provided with holes for concealed arm carrier systems.
- □ **Z5324** 20" x 23" with 4" center faucet holes. Vitreous china, wall hung lavatory provided with holes for concealed arm carrier systems.
- □ **Z5328** 20" x 23" with 8" center faucet holes. Vitreous china, wall hung lavatory provided with holes for concealed arm carrier systems.
- $\square$  **Z5329** 20" x 23" with 12" center faucet holes. Vitreous china, wall hung lavatory provided with holes for concealed arm carrier systems.

### Suffix Options

☐ -**PED** Vitreous china half pedestal.



Z5320 Series 20" x 23" wheelchair lavatory shown with Z6920-CP4 gooseneck sensor faucet (sold separately).

#### Recommended Trim

- ☐ **Z8743-PC** Grid Strainer
- ☐ **Z8700** Series P-Trap
- ☐ **Z8800** Series Stop with Flexible Supplies
- **Z8946-1-NT** ADA Trap, Stop, and **Supply Protectors**

### Optional Trim

- ☐ **Z8746-PC** ADA Grid Strainer
- Z8946-3-NT ADA Trap, Stop, and Supply Protectors for Offset Grid Strainers

Fixtures meet ASME A112.19.2 and CSA B45 standard requirements.



Meets the American Disabilities Guidelines and ANSI A117.1 requirements when lavatory is installed 34" [864mm] from finished floor.

See Zurn One Systems for suggested packages.

This Space is for Architectural/Engineering Approval