

Z5830

19" x 17" Wall Hung Cast Iron Lavatory

Z5830 Series

- 19" x 17" [483mm x 432mm]
- Enameled cast iron
- Faucet holes for single, 4", or 8" centers
- Wall hung lavatory provided with wall hanger or for use with exposed arm carrier systems
- Waste: 1-1/4" O.D.
- Depth: 6-3/4"
- Shipping Weight: 61 lbs.

Engineering Specification

- **Z5831** 19" x 17" enameled cast iron wall hung lavatory. Provided with single faucet hole and hanger plate.
- **Z5834** 19" x 17" enameled cast iron wall hung lavatory. Provided with 4" center faucet holes and hanger plate.
- **Z5838** 19" x 17" enameled cast iron wall hung lavatory. Provided with 8" center faucet holes and hanger plate.

Lavatory With Lugs For Exposed Arm Carrier:

- **Z5831-L** 19" x 17" enameled cast iron wall hung lavatory. Provided with single faucet hole and lugs for exposed arm carrier.
- **Z5834-L** 19" x 17" enameled cast iron wall hung lavatory. Provided with 4" center faucet holes and lugs for exposed arm carrier.
- **Z5838-L** 19" x 17" enameled cast iron wall hung lavatory. Provided with 8" center faucet holes and lugs for exposed arm carrier.



Z5830 Series 19" x 17" wall hung cast iron lavatory shown with Z831R4 faucet (sold separately).

Recommended Trim

- ☐ **Z8743-PC** Grid Strainer
- ☐ **Z8700** Series P-Trap
- ☐ **Z8800** Series Stop with Flexible Supplies
- **Z8946-1-NT** ADA Trap, Stop, and **Supply Protectors**

Optional Trim

- **Z8746-PC** ADA Grid Strainer
- ☐ **Z8946-3-NT** ADA Trap, Stop, and Supply Protectors for Offset Grid Strainers

Fixtures meet ASME A112.19.2 and CSA B45 standard requirements.



Meets the American Disabilities Guidelines and ANSI A117.1 requirements when lavatory is installed 34" [864mm] from finished floor.

See Zurn One Systems for suggested packages.

This Space is for Architectural/Engineering Approval