

Z5314.525.1.07.E6.0

TAG

Z812B4-XL

Gooseneck Faucet

Polished chrome-plated cast brass faucet body with integral shanks, quarter-turn ceramic disc cartridges and a 5-3/8" [137 mm] centerline rigid or swing gooseneck spout. Unit is furnished with a 2.2 gpm [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow), 4" [102 mm] vandal-resistant color-coded metal wrist blade handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers. Lead-free.



Z8743-PC

Grid Drain

Cast Brass, solid-top, open-grid, P.O. plug with 6" 17-gauge tailpiece and cast brass locknut, for sink depths up to 2-1/4". 8", 10" and 12" tailpieces available.



Z8700-PC

1-1/4" Cast Brass P-Trap with Cleanout

Chrome-plated, cast body p-trap,
tubular wall bend 10" CL, die
cast nuts, shallow escutcheon
with 1-1/4" compression Inlet x
1-1/4" compression outlet.



Z8804-XL-LR-PC

Angle Stop

Chrome-plated, solid brass angle stop compression to compression fitting with round wheel handle or loose key as specified. Zurn Lead Compliant* "XL" products are a line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with state laws and local codes that mandate lead content levels. Zurn "XL" products are manufactured with *not more than 0.25% lead content when used with respect to wetted surfaces of pipes and pipe fittings, plumbing fitting and fixtures: California Health & Safety Code § 116875; Vermont 9 VCA § 2470h.



Wall-Mounted Lavatory with Faucet, Drain, P-Trap and Supply Line

Z5314

**20" x 18" Wall-Mounted
Concealed Carrier Arm Lavatory**

Vitreous china wall-mounted lavatory with rear overflow and 4" center faucet holes. Provided with holes for concealed or exposed arm carrier systems. Waste: 1-1/4" O.D. Depth 6-3/4". 1-1/4" O.D. Depth 6-3/4".

