

Z5615.043.01.12.00

TAG

ZEMS6000AV-WS1-IS

1-1/2 Exposed Top Spud 1.6 gpf AquaVantage Electric Integral Sensor Flush Valve for Water Closet

Hardwired Automatic Sensor Flush Valve – Exposed, quiet diaphragm type, chrome-plated, flushometer valve with a polished exterior. Complete with Zurn AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve incorporates a motorized actuator, an integral infrared convergence-type proximity sensor and a manual push-button override into an all-metal, polished chrome-plated housing. Sensor range automatically adjusts to its environment at power up and is powered by a 7.6 VDC power converter. Each power converter can accommodate up to eight flush valves. The valve is complete with high back pressure vacuum breaker, one piece hex coupling nut, adjustable tailpiece, spud coupling and flange for top spud connection. Control stop has internal siphon-guard protection, vandal resistant stop cap, sweat solder kit, and a cast wall flange with setscrew. Internal seals are made of chloramine resistant materials.



Z5955SS-EL

Toilet Seat

Elongated, standard white,
open front toilet seat, less cover,
with stainless steel check hinge.



Z5977-NEO

Neo Seal Gasket Kit for Wall Mount Bowls




Z5610-NUT-EXT-KIT

Wall-Mounted Toilet Retrofit Nut and Washer Kit

Zurn Recommended:

High Performance Carrier System

EZCarry™ horizontal or vertical siphon jet water closet carrier systems with high performance waterway. System includes Dura-Coated cast iron main fitting with hydro-mechanically optimized sweep and extended 2" [51mm] vent, adjustable gasketed faceplate, universal floor mounted pre-fab slotted foot supports, heavy-duty 1/2" [13mm] rear anchor tie down, fixture bolts, trim, stud protectors, bonded "Neo-Seal" gasket, and corrosion resistant, adjustable 3" [76mm] dia. X 6" [152mm] coupling with integral test cap designed to increase flow velocity and line carry. EZCarry system complies with the requirements of ASME A112.6.1M up to a 500 lbs [227 kg] static load rating.



Toilet / Water Closet – Wall-Mounted with Flush Valve, Toilet Seat and Accessory



Z5615-BWL

EcoVantage 1.1 gpf High Efficiency Wall-Mounted Top Spud Toilet

Vitreous china, 1.1 gpf [4.2 Lpf] or greater high efficiency, wall-mounted toilet with siphon jet flushing action and elongated front rim with 1-1/2" top spud. This bowl is designed to perform to industry standards with as little as 1.1 gpf, engineered to provide optimal performance and 20% water savings over conventional 1.6 gpf toilets.

