

Water Closet

Z5616.164.01.91.00

TAG _____

Z6000AV-WS1-BWN

Exposed AquaVantage 1.6 gpf Bedpan Washer Flush Valve

AquaVantage 'AV' Exposed Closet Flush Valve with Bedpan Washer – Exposed, quiet diaphragm-type, chrome-plated, flushometer valve with a polished exterior. Complete with Zurn AquaVantage TPE, chlorine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. Valve is ADA compliant with a non-hold open and no-leak handle feature, high back pressure vacuum breaker, bedpan washer assembly, wall bracket and support rod, one-piece hex coupling nut, adjustable tailpiece, spud coupling, and flange for top spud connection. Control stop has internal siphon-guard protection, vandal-resistant stop cap, sweat solder kit, and a cast wall flange with setscrew. Internal seals are made of chlorine resistant materials.



Z5955SS-EL

Toilet Seat

Elongated, standard white, open front toilet seat, less cover, with stainless steel check hinge.



Z5977-NEO

Neo Seal Gasket Kit for Wall Mount Bowls



Z5610-NUT-EXT-KIT


Wall-Mounted Toilet Retrofit Nut and Washer Kit



Zurn Recommended:

High Performance Carrier System

EZCarry™ horizontal or vertical siphon jet water closet carrier systems with high performance waterway. System includes Dura-Coated cast iron main fitting with hydro-mechanically optimized sweep and extended 2" [51mm] vent, adjustable gasketed faceplate, universal floor mounted pre-fab slotted foot supports, heavy-duty 1/2" [13mm] rear anchor tie down, fixture bolts, trim, stud protectors, bonded "Neo-Seal" gasket, and corrosion resistant, adjustable 3" [76mm] dia. X 6" [152mm] coupling with integral test cap designed to increase flow velocity and line carry. EZCarry system complies with the requirements of ASME A112.6.1M up to a 500 lbs [227 kg] static load rating.



Toilet / Water Closet – Wall-Mounted with Flush Valve, Toilet Seat and Accessory

Z5616-BWL

EcoVantage 1.28 gpf High Efficiency Wall-Mounted Top Spud Toilet

Vitreous china, 1.28 gpf [4.8 Lpf] or greater high efficiency, wall-mounted toilet with siphon jet flushing action and elongated front rim with integral bedpan lugs and 1-1/2" top spud. This bowl is designed to perform to industry standards with as little as 1.28 gpf, engineered to provide optimal performance and 20% water savings over conventional 1.6 gpf toilets.

