

Lavatory

Z5844.545.1.07.E6.0

TAG

Z86100-XL-CP4

Metering Faucet

Polished chrome-plated single basin lavatory, slow-closing metering faucet with an integral brass 3-3/4" [95 mm] centerline spout and a vandal-resistant color-coded metal handle. Easy adjustable cycle time, preset to 10 seconds at 80 PSI. Unit is furnished with a water-conserving 1.0 gpm [3.8 L] (-7M) spray outlet which reduces flow to .25 GPC [.95 L], (complying with ANSI A112.18.1 Standard for flow), 4" [102 mm] centers, integral shank filter, chrome-plated metal cover plate, anti-rotation pins, mounting hardware, 1/2" NPSM coupling nut for standard lavatory risers.



Z8743-PC

Grid Drain

Cast Brass, solid-top, open-grid, P.O. plug with 6" 17-gauge tailpiece and cast brass locknut, for sink depths up to 2-1/4". 8", 10" and 12" tailpieces available.



Z8700-PC

1-1/4" Cast Brass P-Trap with Cleanout

Chrome-plated, cast body p-trap, tubular wall bend 10" CL, die cast nuts, shallow escutcheon with 1-1/4" compression Inlet x 1-1/4" compression outlet.



Z8804-XL-LR-PC

Angle Stop

Chrome-plated, solid brass angle stop compression to compression fitting with round wheel handle or loose key as specified. Zurn Lead Compliant* "XL" products are a line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with state laws and local codes that mandate lead content levels. Zurn "XL" products are manufactured with *not more than 0.25% lead content when used with respect to wetted surfaces of pipes and pipe fittings, plumbing fitting and fixtures: California Health & Safety Code § 116875; Vermont 9 VCA § 2470h.



Cast Iron Wall-Mounted Lavatory with Faucet, Drain, P-Trap and Supply Line

Z5844

20" x 18" Cast Iron Wall-Mounted Lavatory – 4" Centers

20" x 18" enameled cast iron wall-mounted lavatory. Provided with 4" center faucet holes and wall hanger for use with exposed arm carrier systems.

