Model ZW205FP - Fire Pump Pressure Relief Valve **Control Valve Order Form**



Customer:					Date:
Contact:					Email:
Telephone/Fax:					Ref. P. O.
Quantity:					All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.
Size: (Check one) □ 2" □ 2-1/2" □ 3" □ 4" □ 6" □ 8" □ 10"					
Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.					
Function Options: Valve body is ductile iron, epoxy coated					
		•	_	40XL2 Hydraulic Check	valve body is ductile from, epoxy coated
Dadu	0	· Hanai		•	
Boay Check	•	tions: Standard	_	Full Port Globe Body	
one		Standard "A" Option	-	Angle Style Body	
End Connections:					
Liiu C		Standard - ANSI Class 150 Flanges (2" - 10")			
Check		"G" Option		IPS Grooved (2" - 10")	
one		"TH" Option		NPT Threaded (2" - 3")	
		"Y" Option *	-	ANSI Class 300 Flanges (2" - 10")	DIRECTION OF FLOW 与
Main Valve Options:					
Optional:	M	Standard	_	Stainless Steel Seat, Seal Ring Reta	ainer, and Stem Guide
Optional: Check Z OR Z2			-	Visual Position Indicator (Not availal	
Z UK ZZ		"Z2" Option *		Stainless Steel Dry Position Indicate	· · ·
Dilat (Onf	ione:			
Pilot Options: ☑ Standard - 3-Way Gauge Isolation Valve on Inlet Pressure Gauge(UL), and "Wye"					
		Cianadia		Type Strainer	ot
Check one		Standard	-	PV-RLF Pilot (50 - 200 psi)	A 53
O.16		"HP" Option *	*_	PV-RLF Pilot (150 - 300 psi)	
Check		Standard	-	Copper Tubing and Brass Fittings	211 4
one		"SP" Option *	· _	All Stainless Steel Pilotry (replaces Pilot Valve & Copper Tubing)	all Brass Fittings,
Optional		"RV" Option	-	Pilot on Reverse Side	
III & III C Listed FM® Approve					

UL & ULC Listed, FM® Approve

*Adder to standard price applies

1747 Commerce Way Paso Robles, CA 93446 Phone: 855-663-9876 Fax: 805-237-7197

Customer Service Representatives available Monday through Friday 5:30 a.m. to 5:00 p.m., PST Fax completed forms to 805-237-7197, attention: Sales Call 855-663-9876, wilkinscs@zurn.com or visit us online at www.zurn.com



Rev. H

DIRECTION OF FLOW ⇒