TAG




6 [159] REVEAL TRENCH DRAIN SYSTEM W/ STAIN-LESS STEEL VENEER FRAME

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES

Z883-SVF



ENGINEERING SPECIFICATION: Zurn Z883-SVF Channels shall be 40" [1016mm] long, 6" [152mm] wide reveal and have a 4" [102mm] throat. Modular channel sections shall be made of 0% water absorbent Polyethylene. Shall have a positive mechanical connection between channel sections that will not separate during the installation and shall mechanically lock into the concrete surround a minimum of every 10' [254mm]. Channels shall weigh less than 2.31 lbs.[1.05kg] per linear foot, have a smooth, 2" [51mm] radiused self cleaning bottom with a Manning's coefficient of 0.009 and neutral 0% built in slope. Channels shall have rebar clips standard to secure trench in its final location. Shall be provided with standard FS grates that lock down to frame. Zurn 5.375mm [137"] wide reveal Fabricated Stainless Steel Slotted Grate conforming to ASTM specification A351, Grade CF8 (type 304), slotted grate is rated class A per the DIN EN1433 top load classification. Supplied in 20" [508mm] nominal lengths with 0.375" [9.5mm] wide slots, and 0.75" [19mm] bearing depth. Grate has an open area of 13.68 sq. in per ft. [28,956 sq. mm per meter]. The 20 gage Stainless Steel Veneer Frame Assembly conforms to ASTM specification A-240 (type 304). Frames Shall be produced in the U.S.A.

PREFIX OPTIONS (Check/specify appropriate options)

Z Three-foot, Four-inch High Density Polyethylene (HDPE)*

SUFFIX OPTIONS (Check/specify appropriate options)

Outlet Adapters Add/Each

	Closed End Cap 2 [51] No-Hub End Outlet	U3	2 [51] No-Hub Bottom Outlet 3 [76] No-Hub Bottom Outlet	
Frame Options		04	4 [102] No-Hub Bottom Outlet	

____ -SVF Type 304 Stainless Steel Top Veneer Frame*

Grate Options (Load Classifications are per DIN EN1433)

Grate Options (Load Classifications are per DIN EN1433)		Decorative Grate Options (Load Classifications are per DIN EN1433)		
BDC	Black Acid Resistant Epoxy Coated Ductile Grate - Class	BBCD	Bronze Circular Decorative Grate - Class A	
DBG	Ductile Iron Cast Bar Grate - Class B	BDD	Bronze Diagonal Decorative Grate - Class A	
DC	Ductile Iron Solid Cover - Class B	-DCD	Ductile Iron Circular Decorative Grate - Class C	
DGC	Ductile Iron Slotted Grate - Class B	DDD	Ductile Iron Diagonal Decorative Grate - Class A	
GG	Fiberglass Grate - Class A	DOG	Ductile Iron Decorative Grate - Class A	
HPD	Heel-Proof Ductile Slotted Grate - Class B	DWV	Ductile Wave Decorative Grate - Class A	
		HPB	Heel-Proof Bronze Slotted Grate - Class A	
HPP	Heel-Proof Polyethylene Grate - Class A	HPS	Heel-Proof Stainless Steel Slotted Grate - Class A	
RFS	Reinforced Stainless Steel Slotted Grate - Class B	SBG	Stainless Steel Bar Grate - Class B	
RPS	Reinforced Stainless Steel Perforated Grate - Class B	SCD	Stainless Steel Circular Decorative Grate - Class B	
		SDD	Stainless Steel Diagonal Decorative Grate - Class B	
Miscellaneous Options		SMG	Stainless Steel Steel Mesh Grate - Class A	
-VP	Vandal-Proof Lockdown	SOG	Stainless Steel Decorative Grate - Class B	
MADE in the U.S.A. (Load Classifications are per DIN EN1433)		Decorative MAD	DE in the U.S.A. (Load Classifications are per DIN EN1433)	
AWG	Aluminum Wire Grate - Class A	BZ	Bronze Decorative Grate - Class A	
DGC-L	JSA Ductile Iron Slotted Grate - Class B	NBZ	Nickel Bronze Decorative Grate - Class A	
FS	Fabricated Stainless Steel Slotted Grate - Class A*	PSR	Perforated Stainless Steel Raised Grate - Class A	
GG	Fiberglass Grate - Class A	SBG-L	Stainless Steel Bar Grate - Class B	
FS GG PS	Perforated Stainless Steel Grate - Class A	SWG	Stainless Steel Wire Grate - Class A	

Miscellaneous Options

-DB Bottom Dome Strainer

* Regularly furnished unless otherwise specified.

Zurn Industries, LLC | Specification Drainage Operation

1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929 In Canada | **Zurn Industries Limited**

3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

Rev. A Date: 01/27/2017 C.N. No. 136174 Prod. | Dwg. No. Z883-SVF