

Note: All dimensions are for reference only. Do not use for pre-plumbing

## **OPTIONAL ACCESSORIES**

Suffix	Description
AR	Anti-Rotation Pins
CS	Check Stop
FC	2.0 GPM [7.6L] Laminar Flow Control in Base of Spout
HCT	Hot/Cold Text Indexes
LP	Low Profile
LSI	2-1/2" [64mm] Long Swivel Inlets with Integral Stops
PT	1-1/4" [32mm] Cast-Brass P-Trap with a 7-12" [191mm] Long 17-Gauge Wall Bend
RC	Rough Chrome Plated
6M	2.0 GPM [7.6 L] Male Serrated Nozzle Outlet
7M	1.0 GPM [3.8 L] Pressure Compensating Male Spray Outlet
16M	1.0 GPM [3.8 L] Vandal Resistant Pressure Compensating Male Spray Outlet
17M	1.5 GPM [5.7 L] Vandal Resistant Pressure Compensating Male Aerator
18M	1.5 GPM [5.7 L] Vandal Resistant Pressure Compensating Male Laminar Flow

Phone: 1-716-665-1132 ♦ Fax: 1-716-665-1135 ♦ World Wide Web: www.zurn.com In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905/405-8272 Fax: 905/405-1292