



Z5657-BWL1

HET Elongated, Floor Mounted EcoVantage® Flush Valve Toilet

TAG _____

Architectural/Engineering Specification:

Vitreous China, 1.28 gpf [4.8 lpf] or greater high efficiency, floor mounted, bottom outlet toilet with siphon jet flushing action, ZurnSHIELD™ ceramic glaze, and elongated front rim with 1-1/2" back spud. This bowl is designed to perform to industry standards with as little as 1.28 gallons per flush, engineered to provide optimal performance and 20% water savings over conventional 1.6 gpf toilets.

Product Features:

Z5657 HET Series

- Zurn HET Toilet System designed for optimal performance between Zurn fixture and Zurn flush valve at 1.28 gpf (4.8Lpf), 1.6 gpf (6.0 Lpf) or Dual Flush volumes to save water.
- 1.28 gpf (4.8 lpf) or 1.6 gpf (6.0 lpf) or Dual Flush
- 1.28 gpf offers 20% water savings over 1.6 gpf system
- Vitreous china
- ZurnSHIELD™ ceramic glaze creates a permanent surface that protects the fixture by inhibiting the growth of stain and odor causing mold mildew and bacteria, thus reducing the amount of time, chemicals and water to clean the bowl.
- Elongated front rim
- 1-1/2" Back Spud
- 2-1/8" fully glazed trapway
- High efficiency siphon jet flush

Compliance and Certification:

- Complies with ASME A119.2 / CSA B45.1



*This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

Recommended Trim:

Z5955SS-EL

Elongated, standard white, open front toilet seat less cover with stainless steel check hinge.

Z5972-COMB

Closet bolt & wax ring kit.

Note: To ensure system performance:
Minimum Running Water Pressure = 25 psi.

Architectural/Engineering Approval

The information contained in this document is subject to change without notice.
Please contact Zurn for most up to date information.



Z5657-BWL1

HET Elongated, Floor Mounted EcoVantage® Flush
Valve Toilet

TAG _____

Rough-in/Overview dimensions

