

## **OPTIONAL ACCESSORIES**

<ul> <li>AR Anti-Rotation Pins</li> <li>-FC 2.0 GPM [7.6 L] Laminar Flow Control in Base of Spout</li> <li>-G 1-1/4" [32mm] Grid Strainer Drain</li> <li>-HCT Hot/Cold Text Indexes</li> <li>-PT 1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend</li> <li>-140 Restricted 140° Swing Spout</li> <li>-2F 2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator</li> <li>-3F 0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet</li> <li>-4F 2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Laminar Flow Outlet</li> </ul>
G       1-1/4" [32mm] Grid Strainer Drain        HCT       Hot/Cold Text Indexes        PT       1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend        140       Restricted 140° Swing Spout        2F       2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator        3F       0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
-HCTHot/Cold Text Indexes-PT1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend-140Restricted 140° Swing Spout-2F2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator-3F0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
<ul> <li>-PT 1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend</li> <li>-140 Restricted 140° Swing Spout</li> <li>-2F 2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator</li> <li>-3F 0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet</li> </ul>
<ul> <li>-140 Restricted 140° Swing Spout</li> <li>-2F 2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator</li> <li>-3F 0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet</li> </ul>
<ul> <li>-2F</li> <li>-2F</li> <li>2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator</li> <li>-3F</li> <li>0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet</li> </ul>
-3F 0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
-3F 0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
4E 22 CPM [83] Wandal-Resistant Pressure Companyating Female Laminar Flow Outlet
7F 1.0 GPM [3.8 L] Pressure Compensating Female Spray Outlet
-16F 1.0 GPM [3.8 L] Vandal Resistant Pressure Compensating Female Spray Outlet
17F 1.5 GPM [5.7 L] Vandal Resistant Pressure Compensating Female Aerator
19F 1.5 GPM [5.7 L] Anti-Microbial Pressure Compensating Female Laminar Flow Outlet
21F 1.0 GPM [3.8L] Female Laminar Flow Outlet
22F 1.0 GPM [3.8L] Vandal-Resistant Female Laminar Flow Outlet
23F 1.5 GPM [5.7L] Pressure Compensating Female Aerator
ZURN INDUSTRIES, LLC ♦ COMMERCIAL BRASS OPERATION ♦ 2640 SOUTH WORK STREET ♦ FALCONER NY 14733 Phone: 1-800-997-3876 ♦ Fax: 1-919-775-3541 ♦ www.zurn.com In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905/405-8272 Fax: 905/405-1292