Architectural/Engineering Specification:

Vitreous China, 1.1 gpf [4.16 lpf] or greater high efficiency, ADA, floor mounted, bottom outlet toilet with siphon jet flushing action, ZurnSHIELD™ ceramic glaze, and elongated front rim with 1-1/2" top spud. This bowl is designed to perform to industry standards with as little as 1.1 gallons per flush.

Product Features:

- Zurn High Efficiency Toilets and paired performance flush valve systems are designed to exceed industry standards while using as little as 1.1 gallons of water per flush.
- Universal high efficiency toilet can be specified with 1.28 gpf [4.8 lpf], 1.6 gpf [6.0 lpf] or dual flush valves.
- Vitreous china
- ZurnSHIELD™ ceramic glaze creates a permanent surface that protects the fixture by inhibiting the growth of stain and odor causing mold mildew and bacteria, thus reducing the amount of time, chemicals and water to clean the bowl.
- ADA Heaight
- Elongated front rim
- 2-1/8" fully glazed trapway
- High efficiency siphon jet flush action
- Shipping Weight: 65 lbs.

Compliance and Certification:

- Complies with ASME A119.2 / CSA B45.1
- ADA Compliant

WaterSense Meets EPA Criteria Certified by IAPMO R&T

This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

Variation Options:

Z5665-BWL-AM
Z5665 Series top spud toilet

Z5666-BWL-AM
Z5666 Series top spud toilet with integral bedpan lugs

Recommended Trim:

Z5955SS-EL
Elongated, standard white, open front toilet seat less cover with stainless steel check hinge.
Z5972-COMB
Closet bolt & wax ring kit.

Note: To ensure system performance:
Minimum Running Water Pressure = 25 psi.

Architectural/Engineering Approval

The information contained in this document is subject to change without notice.
Please contact Zurn for most up to date information.

Rough-in dimensions/Overview dimensions

28½ [724]
27 [686]
2⅜ [60]
14⅛ [360]
5½ [140]
18½ [470]

FINISHED WALL
1 [25]
I.P.S. SUPPLY
11½ [292]
4¾ [121]±½
[121±13]
16¾ [425]
3⅞ [98]
9¾ [248]
10 [254]
FINISHED FLOOR
6 [152]
MOUNTING
HOLES