

Spec • Com[™] Specified Commercial and Industrial Systems

Drainage solutions for commercial and industrial applications.



Specified Commercial drainage systems are used in applications where heavier loading may occur, such as commercial kitchens, warehouses, and industrial plants that encounter fork lift, hand cart and other heavy traffic loading.

Features and Benefits

- Pre-sloped trench drain systems are offered in high density polyethylene, stainless steel, and fiberglass with Class A, pedestrian and ADA compliant through Class F 200,000 lb. load rating grate options to meet your job site needs
- Z874 systems offer 4-corner grate lock down for dynamic loading situations
- Save labor costs up to 75% with mechanical interlocking connections for fast installation
- Install high volume drainage faster with the Hi-Cap[®] Slotted Drainage System's lightweight sections — for driveway access and loading dock areas
- Systems are available from 4" to 21" pre-sloped with radiused bottom
- · System provides containment of hazardous spills
- Utility trench systems offer dual containment, sub-surface utility passageways while providing surface accessibility for maintenance



Spec•Sport[™] Specified Sport Systems

Trench Drains

Stainless Steel




2890 5' Length Pre-Sloped, Stainless Steel

HDPE



Z886 80" Length Pre-Sloped, HDPE

Fiberglass



Z886-FGF 80" Length, Pre-Sloped with Class F Frame and Grate



Z882 8' Length Pre-Sloped, HDPE



Z806 10' Length Pre-Sloped, Fiberglass

Fabrications

Form No. 220-022. 2/17

Custom fabrications are available upon request for all Zurn Linear Trench systems. Forklift rated available. Frame and grate systems also available for Cast-In-Place applications.

ZURN INDUSTRIES, LLC Linear Drainage Operation

1801 Pittsburgh Avenue, Erie, PA 16502, 855-663-9876

In Canada: ZURN INDUSTRIES LIMITED 7900 Goreway Drive, Unit 10, Brampton, Ontario L6T 5W6, 905-405-8272

INVERT VARIES


2895 5' Length Pre-Sloped, Stainless Steel

2874-12 80" Length Pre-Sloped, HDPE

2874-18 80" Length Pre-Sloped, HDPE



2874-21 80" Length Pre-Sloped, HDPE



Z812 10' Length Pre-Sloped, Fiberglass




Slot Drains


1/8*[232

INVER VARIE

INVERT



Z888-4 40" Length, Non-Sloped Available with 4" extension and heavy-duty frame







and heavy-duty frame

Z888-12 80" Length Also available Z888-18 and -36

Utility Trench – Special Duty

GRATE

Z874-U-4-HD

Z874-U-9-HD

Z874-U-12-HD

Z874-U-18-HD

Z874-U-19-HD

Z874-U-21-HD

900	100	1	
13	190	m	0
24		50	
	1000	A	




Available in medium-duty systems with aluminum frames and covers, or






260

CAPACITY	DIMENSIONS IN INCHES	APPROX. WT.	
GALLONS	тор	HEIGHT	(LBS. [KG])
140	70-1/2 x 35-1/4 [1791 x 895]	30 [762]	328 [149]
200	70-1/2 x 35-1/4 [1791 x 895]	36 [914]	354 [161]




Z888-6 40" Length, Non-Sloped Available with 4" extension and heavy-duty frame



Z891 5' Length, Pre-Sloped Stainless Steel

Catch Basins



2887 24" x 24" Catch Basin Available in 6" x 20" and 12" x 24"

C GRATE WIDTH

[152]

12 [305]

17 [432]

23 [584]

24 [610]

27 [686]

D GRATE HEIGHT

3/4 [19]

1-1/4 [32]

1-3/4 [44]

1-3/4 [44]

1-3/4 [44]

1-3/4 [44]

382 [173]

DIMENSIONS IN INCHES [MM]

B MAX. DEPTH

22 [559]

22 [559]

30 [762]

30 [762]

30 [762]

30 [762]

The Z874-U is a neutral, non-sloped utility drain system.

70-1/2 x 35-1/4 [1791 x 895]

A Throat Width

[102]

[229]

12 [305]

18 [457]

19 [483]

21 [533]

1.855.ONE.ZURN | ZURN.COM

48 [1219]



INVERT VARIES