

# Z5760

## 1.0 gpf Washout Urinal - Back Spud

### Z5760 Series

- 1.0 gpf [3.8 Lpf]
- Vitreous china
- Washout flushing action
- 3/4" top spud
- 2" I.P.S. outlet flange and rubber gasket with integral trap
- 14" extended rim for handicap compliance when installed at proper height
- Shipping Weight: 65 lbs.

### Engineering Specification

- ☐ **Z5760 with Back Spud**  
Vitreous china, 1.0 gpf [3.8 Lpf] low consumption, wall hung urinal with 3/4" back spud and concealed wall hanger brackets.

### Recommended Trim

- ☐ **Z6195AV-WS1** AquaVantage® AV low consumption concealed flush valve for 3/4" back spud urinals.
- ☐ **Z5978-STR** Urinal Dome Strainer

### Optional Water-Savings Trim

- ☐ **Z6195AV-EWS** AquaVantage® AV .5 gpf extra water savings concealed flush valve.



Z5760 Series back spud washout urinal.

URINALS

Fixtures meet ASME A112.19.2 and CSA B45 standard requirements.



Meets the American Disabilities Guidelines and ANSI A117.1 requirements when urinal is installed 17" [432mm] from finished floor.

See Zurn One Systems for suggested packages.

This Space is for Architectural/Engineering Approval

**Zurn Industries, LLC** Commercial Brass and Fixtures Operation

2640 South Work Street · Falconer, NY 14733 · Phone: 716-665-1132 · Fax: 716-665-1135 · [www.zurn.com](http://www.zurn.com)