

Tag

Z5840

20" x 18" Wall Hung Cast Iron Lavatory

Z5840 Series

- 20" x 18" [508mm x 457mm]
- Enameled cast iron
- Faucet holes for single, 4", or 8" centers
- Wall hung lavatory provided with wall hanger or for use with exposed arm carrier systems
- Waste: 1-1/4" O.D.
- Depth: 6-3/4"
- Shipping Weight: 60 lbs.

Engineering Specification

- □ **Z5841** 20" x 18" enameled cast iron wall hung lavatory. Provided with single faucet hole and hanger plate.
- □ **Z5844** 20" x 18" enameled cast iron wall hung lavatory. Provided with 4" center faucet holes and hanger plate.
- □ **Z5848** 20" x 18" enameled cast iron wall hung lavatory. Provided with 8" center faucet holes and hanger plate.

Lavatory With Lugs For Exposed Arm Carrier:

- □ **Z5841-L** 20" x 18" enameled cast iron wall hung lavatory. Provided with single faucet hole and lugs for exposed arm carrier.
- □ **Z5844-L** 20" x 18" enameled cast iron wall hung lavatory. Provided with 4" center faucet holes and lugs for exposed arm carrier.
- □ **Z5848-L** 20" x 18" enameled cast iron wall hung lavatory. Provided with 8" center faucet holes and lugs for exposed arm carrier.



Z5840 Series 20" x 18" wall hung cast iron lavatory shown with Z6915 sensor faucet (sold separately).

Recommended Trim

- □ **Z8743-PC** Grid Strainer
- □ **Z8700** Series P-Trap
- □ **Z8800** Series Stop with Flexible Supplies
- **Z8946-1-NT** ADA Trap, Stop, and Supply Protectors

Optional Trim

- □ **Z8746-PC** ADA Grid Strainer
- □ **Z8946-3-NT** ADA Trap, Stop, and Supply Protectors for Offset Grid Strainers

This Space is for Architectural/Engineering Approval

Fixtures meet ASME A112.19.2 and CSA B45 standard requirements.

Meets the American Disabilities Guidelines and ANSI A117.1 requirements when lavatory is installed 34" [864mm] from finished floor.

See Zurn One Systems for suggested packages.

Zurn Industries, LLC Commercial Brass and Fixtures Operation 2640 South Work Street · Falconer, NY 14733 · Phone: 716-665-1132 · Fax: 716-665-1135 · www.zurn.com