

## Lavatory

Z5111.018.1.07.E6.5

TAG \_\_\_\_\_

### Z825B4-XL

Single Lab Faucet, 5-3/8" Gooseneck Spout, 4" Wrist Blade Handle

Polished chrome-plated single laboratory faucet with integral shank, a quarter-turn ceramic disc cartridge and a 5-3/8" [137 mm] centerline rigid or swing gooseneck spout. Unit is furnished with a 2.0 gpm [7.6 L] variable orifice aerator (complying with ANSI A112.18.1 Standard for flow), a 4" [102 mm] vandal-resistant color-coded metal wrist blade handle, mounting hardware and a 1/2" NPSM coupling nut for standard lavatory riser. Lead-free.



### Z8743-PC

Grid Drain

Cast Brass, solid-top, open-grid, P.O. plug with 6" 17-gauge tailpiece and cast brass locknut, for sink depths up to 2-1/4". 8", 10" and 12" tailpieces available.



### Z8700-PC

1-1/4" Cast Brass P-Trap with Cleanout

Chrome-plated, cast body p-trap, tubular wall bend 10" CL, die cast nuts, shallow escutcheon with 1-1/4" compression Inlet x 1-1/4" compression outlet.



### Z8804-XL-LR-PC

Angle Stop

Chrome-plated, solid brass angle stop compression to compression fitting with round wheel handle or loose key as specified. Zurn Lead Compliant\* "XL" products are a line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with state laws and local codes that mandate lead content levels. Zurn "XL" products are manufactured with \*not more than 0.25% lead content when used with respect to wetted surfaces of pipes and pipe fittings, plumbing fitting and fixtures: California Health & Safety Code § 116875; Vermont 9 VCA § 2470h.



### Z8946-1-NT

ADA Combination Trap and Supply Wrap Protector Kit

One trap and two supplies, satin white PVC resin, with a 3/8" nominal wall – resists thermal transfer.



## Drop-In Lavatory with Faucet, Drain, P-Trap, Supply Line and Trap Wrap

### Z5111

Single Hole Countertop Lavatory

20" x 17" vitreous china, self rimming, countertop lavatory with single faucet hole. Front overflow design. Waste: 1-1/4" O.D.

