

Water Closet

Z5655.001.01.03.00

TAG _____

Z6000AV-WS1

AquaVantage® 'AV' 1.6 gpf Exposed Closet Flush Valve
AquaVantage® 'AV' Exposed Closet Flush Valve – Exposed, quiet diaphragm-type, chrome-plated flushometer valve with a polished exterior. Complete with Zurn AquaVantage TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve is ADA compliant with a non-hold open and no-leak handle feature, high back pressure vacuum breaker, one-piece hex coupling nut, adjustable tailpiece, spud coupling, and flange for top spud connection. Control stop has internal siphon-guard protection, vandal-resistant stop cap, sweat solder kit, and a cast wall flange with setscrew. Internal seals are made of chloramine resistant materials.



Z5955SS-EL

Elongated, Standard White, Open Front Toilet Seat
Elongated, standard white, open front toilet seat, less cover, with stainless steel check hinge.



Z5972-COMB

Closet Bolt and Wax Ring Kit



Toilet / Water Closet – Floor-Mounted with Flush Valve, Toilet Seat and Accessory

Z5655-BWL

EcoVantage 1.28 gpf High Efficiency or 1.6 gpf Flush Valve System with Top Spud, Floor-Mounted Toilet
Vitreous China, 1.28 gpf [4.8 Lpf] or greater high efficiency, floor-mounted, bottom outlet toilet with siphon jet flushing action and elongated front rim with 1-1/2" top spud. This bowl is designed to perform to industry standards with as little as 1.28 gpf, engineered to provide optimal performance and 20% water savings over conventional 1.6 gpf toilets.

