

## Water Closet

Z5665.031.01.03.00

TAG \_\_\_\_\_

### ZER6000AV-WS1-CPM

1-1/2" Exposed Top Spud 1.6 gpf AquaVantage Flush Valve with Battery Sensor E-Z Flush Metal Cover for Water Closet AquaSense 'AV' Exposed Closet Flush Valve – Exposed, quiet-diaphragm-type, chrome-plated, flushometer valve with a polished exterior. Complete with Zurn AquaVantage TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve incorporates a 6VDC motor actuator, a battery powered automatic sensor, high impact resistant polycarbonate housing and chrome-plated metal cover with manual override push button, high back pressure vacuum breaker, one-piece hex coupling nut, adjustable tailpiece, spud coupling and flange for top spud connection. Control stop has internal siphon-guard protection, vandal-resistant stop cap, sweat solder kit, and a cast wall flange with setscrew. Internal seals are made of chloramine resistant materials.



### Z5955SS-EL

Elongated, Standard White, Open Front Toilet Seat  
Elongated, standard white, open front toilet seat, less cover, with stainless steel check hinge.



### Z5972-COMB

Closet Bolt and Wax Ring Kit



These dimensions and specifications are subject to change without notice.  
Fixture dimensions meet ANSI/ASME standard A112.19.2 and CAN/CSA B45 requirements.

## Toilet / Water Closet – Floor-Mounted with Flush Valve, Toilet Seat and Accessory

### Z5665-BWL

EcoVantage 1.28 gpf High Efficiency or 1.6 gpf Flush Valve System with Floor-Mounted ADA Compliant Toilet Vitreous china, high efficiency, elongated. siphon-jet flushing action, ADA height, floor-mounted toilet with 4-1/8" back outlet rough-in, and 1-1/2" top spud. Includes bolt caps.

