

Service Sink

Z5898.02.215.0.00.02

TAG _____

Z5900-IP3

Trap Standard 3" IPS outlet



Z843M1-RC

Service Sink Faucet with 6" Integral Vacuum Breaker Spout with Hose Thread Outlet and Pail Hook, Adjustable Swivel Inlets, 2-1/2" Lever Handles, Rough-Chrome Finish

Rough chrome-plated cast brass 8" [203mm] sink faucet with quarter-turn ceramic disc cartridges, 3/8" [10mm] short swivel inlets providing adjustable centers from 7-1/4" [184 mm] to 8-3/4" [222 mm], integral service stops and a 6" [152 mm] centerline cast brass spout with chemical resistant vacuum breaker, 3/4" hose threaded outlet, pail hook and adjustable wall brace. Unit is furnished with 2-1/2" [64mm] vandal-resistant color-coded metal lever handles. (Note: Atmospheric vacuum breaker not intended for continuous pressure applications.)



HH

Hose and Bracket

Hose and Bracket – Heavy-duty 5/8", 30" long cloth-reinforced flexible rubber hose with 3/4" brass coupling at one end. Bracket is 5" long x 3" wide, 20-gage type 304 stainless steel with rubber grip.



Utility Service Sink with Drain Assembly, Faucet and Accessory

Z5898

Cast Iron Service Sink 8" Center Holes



24" x 20" enameled cast iron service sink with 12" backsplash and 8" center faucet holes. Provided with hanger plate and U-type stainless steel rim guard. For use with trap standard. Depth: 12-3/4".

