


Z9A-PRED PVDF REDUCING COUPLING

Engineering Specification:

ASTM-F1673, UL Classified
ZURN Z9A-PRED REDUCING COUPLING –
Polyvinylidene fluoride reducing fitting assembly.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]		
	Reducer Size	E	L
Z9A-PRED-2 x112	2 x 1-1/2 [51 x 38]	1-1/2 [38]	2-5/8 [67]
Z9A-PRED-3 x 112	3 x 1-1/2 [76 x 38]	2-1/32 [52]	3-7/32 [82]
Z9A-PRED-3 x 2	3 x 2 [76 x 51]	2-1/16 [52]	3-9/16 [90]
Z9A-PRED-4 x 112	4 x 1-1/2 [102 x 38]	2-7/8 [73]	4-5/32 [106]
Z9A-PRED-4 x 2	4 x 2 [102 x 51]	2-27/32 [72]	4-3/8 [111]
Z9A-PRED-4 x 3	4 x 3 [102 x 76]	1-29/32 [48]	4-7/32 [107]


Z9A-PMA PVDF MALE THREAD ADAPTER

Engineering Specification:

ASTM-F1673, UL Classified
ZURN Z9A-PMA MALE ADAPTER – Polyvinylidene
fluoride male adapter fitting assembly. Use Teflon
tape on threads.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	E	L
Z9A-PMA-112	1-1/2 [38]	1-5/16 [33]	1-5/16 [33]
Z9A-PMA-2	2 [51]	1-11/32 [34]	1-9/16 [40]
Z9A-PMA-3	3 [76]	2-5/32 [55]	2-13/16 [71]
Z9A-PMA-4	4 [102]	2-1/16 [52]	3-1/32 [77]

Z9A-PFA PVDF FEMALE THREAD ADAPTER – NPT


Engineering Specification:

ASTM-F1673, UL Classified
ZURN Z9A-PFA FEMALE THREAD ADAPTER –
Polyvinylidene fluoride female thread adapter fitting
assembly. Use Teflon tape on threads.

Note: All sizes also available in straight thread.
Designate Z9A-PFAS when ordering.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	E	L
Z9A-PFA-112	1-1/2 [38]	7/32 [6]	2 [51]
Z9A-PFA-2	2 [51]	5/32 [4]	2-7/32 [56]
Z9A-PFA-3	3 [76]	5/16 [8]	3-9/16 [90]
Z9A-PFA-4	4 [102]	11/32 [9]	3-21/32 [93]