

# MODEL ZW205E - Pressure Relief Valve with Solenoid Shut-off Valve



## Control Valve Order Form

Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

### Required Valve Information

Quantity: \_\_\_\_\_

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Size: (Check one)    **1-1/4"**    **1-1/2"**    **2"**    **2-1/2"**    **3"**    **4"**    **6"**    **8"**    **10"**    **12"**    **14"**    **16"**

**Caution:** The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

### Function Options:

**Valve body is ductile iron, epoxy coated**

- Isolation Valves, Inlet Pressure Gauge, and "Wye" Type Strainer**
- Check all that apply
- "C" Option \* - Check Valve with Isolation Valve
  - "L" Option \* - Closing Speed Control (Standard on 4" or smaller)
  - "O" Option \* - Opening Speed Control

### Body Options:

- Check one
- Full Port Globe Body**
- "A" Option \* - Angle Style Body (1-1/4" - 10")
  - "R" Option \* - Reduced Port Body (3" - 10" Flanged only)

### End Connections:

- Check one
- ANSI Class 150 Flanges (1-1/2" - 16")**
- "G" Option - IPS Grooved (1-1/2" - 10")
  - "TH" Option - NPT Threaded (1-1/4" - 3")
  - "Y" Option \* - ANSI Class 300 Flanges (1-1/2" - 16")

### Main Valve Options:

- Stainless Steel Seat, Seal Ring Retainer and Stem Guide**
- Check all that apply
- "Z" Option \*1 - Visual Position Indicator
  - "SO" Option \*1 - Limit Switch Open Trip
  - "SC" Option \*1 - Limit Switch Closed Trip
  - "SD" Option \*1 - Limit Switch Dual Trip

### Pilot Options:

- Check one
- Pressure Relief Pilot (50 - 200 psi)**
- "LP3" Option - PV-RLF Pilot (5-15 psi)
  - "LP2" Option - PV-RLF Pilot (10-35 psi)
  - "LP" Option - PV-RLF Pilot (30-90 psi)
  - "HP" Option \* - PV-RLF Pilot (150-300 psi)
- 
- Check one
- Copper Tubing and Brass Fittings**
- "SP" Option \* - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included)
  - "SH" Option \* - Stainless Steel Braided Hoses (replaces Copper Tubing)
- 
- Check one
- "NC" Option - Normally Closed (energize to open) Main Valve, 120vac Solenoid
  - "NO" Option - Normally Open (energize to close) Main Valve, 120vac Solenoid
  - "24NC" Option - Normally Closed (energize to open) Main Valve, 24vac Solenoid
  - "24NO" Option - Normally Open (energize to close) Main Valve, 24vac Solenoid
  - "NS" Option \* - Non-Standard Solenoid specify Voltage/Frequency/AC/DC/Operation  
V \_\_\_\_\_ Hz \_\_\_\_\_ AC/DC \_\_\_\_\_ NO/NC \_\_\_\_\_
- 
- Check all that apply
- "MO" Option \* - Manual Operator on Solenoid Valve (to control during power failure)
  - "RV" Option - Pilot Installed on Reverse Side
  - "GL" Option \* - Liquid Filled Gauge



1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurn.com  
or visit us online at www.zurn.com

