

MODEL ZW221 - One Way Altitude Level Control Valve

Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Quantity: _____

Size: (Check one) 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 6" 8" 10" 12" 14" 16"

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Valve body is ductile iron, epoxy coated

Function Options:


- Check all that apply Standard
- "D" Option * - Delayed drawdown level before valve reopens (3 - 20ft)
 - "C" Option * - Check Valve with Isolation Valve
 - Standard - Closing Speed Control
 - "O" Option * - Opening Speed Control (Standard on 4" or smaller)

Body Options:

- Check one
- Standard - Full Port Globe Body
 - "A" Option - Angle Style Body (1-1/4" - 10")
 - "R" Option - Reduced Port Body (3" - 10" Flanged only)

End Connections:

- Check one
- Standard - ANSI Class 150 Flanges (1-1/2" - 16")
 - "G" Option - IPS Grooved (1-1/2" - 10")
 - "TH" Option - NPT Threaded (1-1/4" - 3")
 - "Y" Option * - ANSI Class 300 Flanges (1-1/2" - 16")



Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 - Standard¹ - Visual Position Indicator
 - "SO" Option *¹ - Limit Switch Open Trip
 - "SC" Option *¹ - Limit Switch Closed Trip
 - "SD" Option *¹ - Limit Switch Dual Trip

Pilot Options:

- Standard - Isolation Valves, Inlet and Pressure Gauges, and "Wye" Type Strainer

- Must check one
- "L1" Option - 5'-55' Adjustment Range
 - "L2" Option - 45'-85' Adjustment Range
 - "L3" Option - 75'-230' Adjustment Range

Enter Desired Setting: _____ Ft

- Check all that apply
- Standard - Stainless Steel Braided Hoses and Brass Fittings
 - "F" Option - Atmospheric "Wet" Drain
 - "RV" Option - Pilot Installed on Reverse Side
 - Standard - Liquid Filled Pressure Gauges on Inlet and Reservoir Sensing with Isolation Valves and Reservoir Line Flush Valve

*Adder to standard price applies

¹Limit switch and position indicator options cannot be combined; Limit switch will replace visual position indicator

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

