Architectural/Engineering Specification:

Polished chrome-plated cast brass 8" [203mm] sink faucet with quarter turn ceramic disc cartridges, 3/8" [10mm] short swivel inlets providing adjustable centers from 7-1/4"[184mm] to 8-3/4" [222mm], integral service stops and a 9-1/2" [241mm] tubular brass swing spout with a 2.2 GPM [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow). Unit is furnished with 2 1/2" [64mm] vandal-resistant color-coded metal lever handles. Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface

Compliance and Certification:

- Complies with ASME A112.18.1/CSA B125.1
- Lead Free Compliant
- ADA Compliant



Aerator Options:

	Flow rate GPM [LpM]	Vandal Resistant	Pressure Compressation	Outlet Type
-2F	2.2[8.3]	✓	✓	Aerator
-3F	0.5[1.9]	✓	✓	Spray
-4F	2.2[8.3]	✓	✓	Laminar
-7F	1.0[3.8]		✓	Spray
-16F	1.0[3.8]	✓	✓	Spray
-17F	1.5[5.7]	✓	✓	Aerator
-18F	1.5[5.7]	✓	✓	Laminar
-19F	1.5[5.7]		✓	Laminar
-21F	1.0[3.8]		✓	Laminar
-22F	1.0[3.8]	✓	✓	Laminar
-23F	1.5[5.7]		✓	Areator

Suffix Options:

-CS Check Stops

-LSI 2-1/2" [64mm] Long Swivel Inlets

Architectural/Engineering Approval

The information contained in this document is subject to change without notice.

Please contact Zurn for most up to date information.





Z843J1-XL SINK FAUCET

TAG _____

Rough-in dimensions/Overview dimensions



