

4" CENTERSET GOOSENECK

Z812Q3

TAG	



Engineering Specifications: Zurn AquaSpec Z812Q3

Polished chrome-plated cast brass faucet body with integral shanks, quarter turn ceramic disc cartridges and a 6" [152mm] centerline cast brass aerated outlet vacuum breaker spout. Unit is furnished with a 2.2 GPM [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow), 2" [51mm] vandal-resistant color-coded metal dome lever handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers. (Note: Atmoshperic vacuum breaker not intended for continuous pressure applications.)

2[51] $\frac{4}{102}$ $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [23] $\frac{7}{8}$ [24] $\frac{7}{8}$ [25] $\frac{7}{8}$ [27] $\frac{7}{8}$ [27] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [29] $\frac{7}{8}$ [29] $\frac{7}{8}$ [20] $\frac{7}{8}$ [20] $\frac{7}{8}$ [21] $\frac{7}{8}$ [21] $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [23] $\frac{7}{8}$ [23] $\frac{7}{8}$ [23] $\frac{7}{8}$ [24] $\frac{7}{8}$ [25] $\frac{7}{8}$ [27] $\frac{7}{8}$ [28] $\frac{7}{8}$ [29] $\frac{7}{8}$ [29] $\frac{7}{8}$ [29] $\frac{7}{8}$ [20] $\frac{7}{8}$ [20] $\frac{7}{8}$ [21] $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [23] $\frac{7}{8}$ [23] $\frac{7}{8}$ [23] $\frac{7}{8}$ [24] $\frac{7}{8}$ [25] $\frac{7}{8}$ [27] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [29] $\frac{7}{8}$ [29] $\frac{7}{8}$ [29] $\frac{7}{8}$ [29] $\frac{7}{8}$ [29] $\frac{7}{8}$ [20] $\frac{7}{8}$ [20] $\frac{7}{8}$ [20] $\frac{7}{8}$ [20] $\frac{7}{8}$ [21] $\frac{7}{8}$ [21] $\frac{7}{8}$ [22] $\frac{7}{8}$ [22] $\frac{7}{8}$ [23] $\frac{7}{8}$ [23] $\frac{7}{8}$ [23] $\frac{7}{8}$ [23] $\frac{7}{8}$ [24] $\frac{7}{8}$ [25] $\frac{7}{8}$ [25] $\frac{7}{8}$ [27] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [28] $\frac{7}{8}$ [29] \frac

Note: All dimensions are for reference only. Do not use for pre-plumbing

OPTIONAL ACCESSORIES

Suffix	(Description
	-CS	Check Stops
	-G	1-1/4" [32mm] Grid Strainer Drain
	-HCT	Hot/Cold Text Indexes
	-P	1-1/4" [32mm] Pop-up Drain
	-PT	1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend
	-2F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator
	-3F	0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
	-4F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Laminar Flow Outlet
	-5F	2.0 GPM [7.6 L] Female Spray Outlet
	-7F	1.0 GPM [3.8 L] Pressure Compensating Female Spray Outlet
	-16F	1.0 GPM [3.8L] Vandal-Resistant Pressure Compensating Female Spray Outlet
	-17F	1.5 GPM [5.7L] Vandal-Resistant Pressure Compensating Female Aerator
	-18F	1.5 GPM [5.7L] Vandal-Resistant Pressure Compensating Female Laminar Flow Outlet
	-19F	1.5 GPM [5.7 L] Anti-Microbial Pressure Compensating Female Laminar Flow Outlet
	-21F	1.0 GPM [3.8L] Pressure Compensating Female Laminar Flow Outlet
	-22F	1.0 GPM [3.8L] Vandal-Resistant Pressure Compensating Female Laminar Flow Outlet
	-23F	1.5 GPM [5.7L] Pressure Compensating Female Aerator
	-24F	0.35 GPM [1.3 L] Pressure Compensating Female Spray Outlet
	-25F	0.35 GPM [1.3 L] Vandal-Resistant Pressure Compensating Female Spray Outlet

ZURN INDUSTRIES, LLC ♦ COMMERCIAL BRASS OPERATION ♦ 2640 SOUTH WORK STREET ♦ FALCONER NY 14733 Phone: 1-800-997-3876 ♦ Fax: 1-919-775-3541 ♦ www.zurn.com