


Z888-36-HPD

SPECIFICATION SHEET

HI-CAP SLOTTED DRAINAGE SYSTEM WITH HEELPROOF DUCTILE IRON GRATE FOR 36 [914] CORRUGATED PIPE OR EQUIVALENT

TAG	

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



ENGINEERING SPECIFICATION: Zurn Z888-36-HPD Slotted Drain channel is 80 [2032] long, 31.75 [806] deep invert, 23 [584] wide with a 1.75 [44] throat width, made from LLDPE linear Low Density Polyethylene. Channels have a mechanical tongue and groove and bolted connection, mechanically lock into the concrete surround every 5 [127] along its length, channels weigh 10.2 lbs. per foot [15.2 kg per meter]. Channel has a smooth 2.5 [64] radiused bottom with a smooth .011 Manning's coeficient, and neutral non-sloping body. Top reveal is non removable and is the finish at the surface, System is anchored into the concrete with Rebar clips or physical anchors every 5 [127] to 10 [254] along the channel body. Integral Rebar Clips are standard. Minimum 2000 psi concrete encasement shall include longitudinal #4 0.5 [13] rebar along chairs on either side of the trench neck. System The Channel has a non-removable ADA compliant, heelproof ductile Iron Frame/Grate conforming to ASTM A536-84, Grade 80-55-06. Ductile Iron is capable of Supporting Class C Loading per DIN EN1433 top load classifications.

PREFIX OPTIONS

Z 80 [2032] linear low density polyethylene modular drain channel with integral top frame.*

FRAME OPTIONS (must choose one)

HPG	Heelproof Ductile Iron Galvanized frame/grate
DYN	Reinforcing Schedule For Higher Loading

SUFFIX OPTIONS

End Cap
12 [305] No Hub End Outlet
18 [457] No Hub End Outlet
24 [610] No Hub End Outlet
36 [914] No Hub End Outlet
Transition from -18 - 36 [457 - 914]

*Regularly Furnished Unless Otherwise Specified

REV. A DATE: 09/17/10 C.N. NO. 111680 DWG. NO. 64005 PRODUCT NO. Z888-36-HPD