




Z1201-ND4

EZCARRY® ADJUSTABLE HORIZONTAL HIGH PERFORMANCE
BACK-TO-BACK SIPHON JET NO-HUB WATER CLOSET CARRIER
SYSTEM

SPECIFICATION SHEET

TAG _____

Design and Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



Product Number	Approx. Wt. lbs [kg]
Z1201-ND4	104 [47]

Note:

1. Z coupling, Min. 'P' Dim. Obtainable=2 [51].EZ-Set™ Coupling, Min. 'P' Dim. Obtainable=4-1/4 [108] or 2-1/16 [52] for 12 [305] NPT.
2. Feet bolted to floor using min. 1/2 [13] dia. anchors.

ENGINEERING SPECIFICATION: ZURN Z1201-ND4

EZCarry® horizontal siphon jet water closet carrier system with high performance waterway and 4" [102mm] no-hub connections. System includes Dura-Coated cast iron double main fitting with hydro-mechanically optimized sweep and extended 2" [51mm] vent, adjustable gasketed faceplates, floor mounted pre-fab slotted foot supports with top anchoring pre-fab support base, fixture bolts, trim, stud protectors, bonded "Neo-Seal" gaskets, and corrosion resistant, adjustable 3" [76mm] dia. X 6" [152mm] couplings with integral test caps designed to increase flow velocity and line carry. EZCarry® system complies with the requirements of ASME A112.6.1M up to a 500 lbs [227 kg] static load rating.

OPTIONS (Check/specify appropriate options)

___ Z1201-ND4 4 [102] Hub Back-to-Back Inlet (Double)

PREFIXES

___ Z D.C.C.I. System with Zurn ZZ Adjustable Coupling*
___ ZQ D.C.C.I. System with NPT Faceplate, Non-Adjustable Coupling

SUFFIXES

___ -A Auxiliary Support Assembly (For 'P' Dim. Greater than 18 [457])	___ -F Floor Mounted, Back Outlet Fixture Support
___ -CC Corrosion Resistant Cast Iron Coupling (2-1/4 [57] to 12 [305])	___ -G Galvanized Cast Iron
___ -CE EZ-Set™ Coupling (NPSM 6 [152], 12 [305] or custom) (NPT 12 [305] or custom)	___ -M Auxiliary Foot Support (for 'P' Dim. 7 thru 18 [178 thru 457])
___ -CL Custom Length Standard Coupling with Integral TestCap (Specify Length 4, 8, 10, 12 [102, 203, 254, 305])	___ -RYK17 One Piece Unistrut Pre-Fab Foot Support
___ -CS 2-1/4 [57] Polymer Coupling with Integral Test Cap	___ -VP Vandal-Proof Trim
	___ -X2 2 [51] Carrier Foot Extension Assembly
	___ -X3 3 [76] Carrier Foot Extension Assembly
	___ -45 Finishing Frame for Siphon Jet System
	___ -50 Flush Valve Supply Support for Water Closets

* Regularly furnished unless otherwise specified.

⚠ **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

⚠ **ADVERTENCIA:** Cáncer y daño reproductivo - www.P65Warnings.ca.gov

⚠ **AVERTISSEMENT:** Cancer et effets néfastes sur la reproduction - www.P65Warnings.ca.gov

Zurn Industries, LLC | Specification Drainage Operation
1801 Pittsburgh Avenue, Erie, PA USA 16502, Ph. 855.663.9876

In Canada | Zurn Industries Limited
7900 Goreway Drive, Unit 10, Brampton, Ontario L6T 5W6, Ph. 877.892.5216

www.zurn.com

Rev. N
Date: 01/02/23
C.N. No. 144897
Patent zurn.com/patents
Prod. | Dwg. No. Z1201-ND4