
Z125-E

8-3/8 [213] DIAMETER ROOF DRAIN W/STATIC EXTENSION

SPECIFICATION SH	EET
------------------	-----

TAG _____

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



А	Approx.	Dome Open
Pipe Size	Wt.	Area
In.[mm]	Lbs. [kg]	Sq. In. [cm²]
2,3,4 [51,76,102]	18 [8]	43 [277]

ENGINEERING SPECIFICATION: ZURN Z125-E

8-3/8" [213mm] Diameter roof drain, Dura-Coated cast iron body with combination membrane flashing clamp/gravel guard, static extension with gasket and low silhouette Poly-Dome.

OPTIONS (Check/specify appropriate options)

PIPE SIZE 2,3,4[51,76,102] 2 [51] 3 [76] 4 [102] 2,3,4[51,76,102] 2,3,4[51,76,102]	(Specify size/type) OUTLE IC Inside Caull IP Threaded IP Threaded IP Threaded IP Threaded NH No-Hub NL Neo-Loc	
PREFIXES Z D.C.C.I. Body with Poly-Dom ZA D.C.C.I. Body with Aluminum ZC D.C.C.I. Body with Low Silho SUFFIXES -AR Acid Resistant Epoxy Coate -C Underdeck Clamp -DP Top-Set® Roof Deck Plate (Replaces both the -C and -I Replaces both the -C and -I FG Flush Grate -G Galvanized Cast Iron -R Roof Sump Receiver -SC Secondary Clamping Collar -SS Stainless Mesh Screen Over	m Dome (4-1/4 [108] Dome In	Height) 4 [108] Dome Height) Neo-Loc Test Cap Gasket (2,3,4 [51,76,102] NL Bottom Outlet Only)

^{*} Regularly furnished unless otherwise specified.

www.zurn.com

Zurn Industries, LLC | Specification Drainage Operation
1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929
In Canada | Zurn Industries Limited
3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

Rev. F

Date: 10/03/2017 C.N. No. 138282

Prod. | Dwg. No. Z125-E