




# Z1172-HD

## LARGE CAPACITY GREASE INTERCEPTOR W/ HEAVY-DUTY COVER

SPECIFICATION SHEET

TAG \_\_\_\_\_

Dimensional Data (inches and [ mm ]) are Subject to Manufacturing Tolerances and Change Without Notice



Size	Inlet/ Outlet Size	Flow Rate G.P.M. [L]	Capacity		No. of Covers	Approx. Wt. Lbs. [kg]	Dimensions in Inches			
			Water Gal. [L]	Grease Lbs. [kg]			C#	D/E	F	G
900	3 [76]	75 [284]	65 [246]	150 [68]	1	420 [191]	26 3/4 [679]	18 1/2 [470]	36 [914]	28 5/8 [727]
1000		100 [378]	110 [416]	200 [91]		515 [234]	33 [838]	23 [584]	42 3/4 [1086]	33 5/8 [854]
1100		125 [472]	150 [567]	250 [114]		860 [390]	33 1/8 [841]	24 1/2 [622]	49 1/4 [1251]	40 [1016]
1200	4 [102]	150 [567]	195 [737]	300 [136]	2	975 [442]	33 3/4 [857]	25 1/4 [641]	56 [1422]	41 5/8 [1057]
1300		200 [756]	270 [1021]	400 [182]		1160 [526]	38 1/2 [978]	29 7/8 [759]	61 [1549]	43 5/8 [1108]
1400	5 [127]	250 [945]	465 [1758]	500 [227]	2	1510 [685]	44 [1118]	36 [914]	71 [1803]	51 5/8 [1311]
1500		300 [1134]	665 [2514]	600 [272]		1970 [894]	49 1/4 [1251]	39 5/8 [1006]	80 [2032]	58 5/8 [1489]
1600	6 [152]	350 [1323]	865 [3278]	700 [318]	3	2300 [1043]	53 1/2 [1359]	43 7/8 [1114]	87 [2210]	63 5/8 [1616]
1700		400 [1512]	1095 [4139]	800 [363]		2670 [1211]	57 1/4 [1454]	47 5/8 [1210]	94 [2388]	67 [1702]
1800		450 [1701]	1280 [4838]	900 [409]		2980 [1352]	58 1/4 [1480]	48 5/8 [1235]	100 [2540]	72 [1829]
1900		500 [1890]	1440 [5443]	1000 [454]		3100 [1406]	60 1/4 [1530]	51 5/8 [1311]	104 [2642]	74 [1880]

**ENGINEERING SPECIFICATION: ZURN Z1172-HD**

Large capacity Acid Resistant Coated interior and exterior fabricated steel grease interceptor, rated at \_\_\_\_ GPM and \_\_\_\_ Lbs. grease capacity, with internal air relief by-pass, bronze cleanout plug and visible double wall trap seal with removable pressure equalizing/flow diffusing baffle. Gasketed non-skid heavy-duty secured traffic cover rated at 10,000 lbs. [4536 Kg.] maximum load with removable lift handles, complete with flow control fitting. Regularly furnished with inlet and outlet in high position.

**OPTIONS** (Check/specify appropriate options)

**PREFIXES**

- \_\_\_\_ Z Acid Resistant Coated Fabricated Steel\*
- \_\_\_\_ ZS All Type 304 Fabricated Stainless Steel

**SUFFIXES**

- \_\_\_\_ -E Acid Resistant Coated Interior and exterior fabricated steel extension section. (Specify 'C' Dim. required) for recessed installation.  
Note: For (-HD) Heavy-duty applications, the extension must be built integral to the base interceptor unit.
- \_\_\_\_ -K Anchor flange 1-3/4 [44] down from top and 2 [51] wide.
- \_\_\_\_ -KC Anchor flange 1-3/4 [44] down from top and 2 [51] wide with clamp collar.
- \_\_\_\_ -L Angle type (Z1108-L) flow control device.

<b>REV.</b>	<b>DATE: 7/2/08</b>	<b>C.N. NO. 98725</b>
<b>DWG. NO. 83831</b>	<b>PRODUCT NO. Z1172-HD</b>	

\*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED