




Z1204-N-PF

ADJUSTABLE VERTICAL SIPHON JET-NO-HUB W/ PREFAB FEET

SPECIFICATION SHEET

TAG _____

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



Note:

1. Min. 'P' Dim. Obtainable = 2 [51]
2. 2 [51] No-Hub vent connection regularly furnished on right hand side. Left hand available when specified (Suffix-VL)
3. Auxiliary inlet available right (-JR) or left (-JL) or both sides (-JJ) when specified.
4. Feet bolted to floor using min. 1/2 [13] dia. bolts and back slots on carrier feet.
5. Back anchor foot required for secure installation.

Product No.	Dimensions In Inches					Approx. Wt.Lbs. [kg]
	A	D	E	H	N	
Z1204-N4-PF	4 [102]	5 [127]	6 5/8 [168]	5 1/2 [140]	8 7/8 [225]	80 [36]
Z1204-N5-PF	5 [127]	5 1/2 [140]	6 5/8 [168]	6 1/2 [165]	9 3/8 [238]	85 [39]
Z1204-N6-PF	6 [152]	6 [152]	7 1/8 [181]	6 1/2 [165]	10 3/8 [264]	95 [43]

ENGINEERING SPECIFICATION: ZURN Z1204-N-PF Adjustable, vertical siphon jet water closet "Rigid System" with () size No-Hub connections and () side inlets. Complete with Dura-Coated cast iron right hand, left hand, or double main fitting, with 2 [51] vent, adjustable gasketed faceplate, prefab foot supports, corrosion resistant adjustable ABS coupling with integral test cap, fixture bolts, trim, and stud protectors. Rear anchor tie down and bonded "Neo-Seal" gasket.

PRODUCT/DEFINITION

___ Z1204-N()-PF No-Hub Stack, Single Inlet, 2 [51] Right Hand Vent

PREFIXES

- ___ Z D.C.C.I. System with Zurn "ZZ" Adjustable Coupling*
- ___ ZC D.C.C.I. System with Compression Fit Faceplate
- ___ ZQ D.C.C.I. System with NPT Faceplate, Non-Adjustable Coupling

SUFFIXES

- | | |
|---|--|
| <ul style="list-style-type: none"> ___ -A Auxiliary Support Assembly (For P-Dim. Greater than 18 [457]) ___ -B Blowout Type Fixture Support ___ -BC Back Cleanout ___ -CC Corrosion Resistant Cast Iron Coupling (6 to 12 [152] to [305]) ___ -CL Coupling Length Greater than 12 [152] (Specify Length Required.) ___ -F Floor Mount, Back Outlet Fixture Support ___ -G Galvanized Cast Iron ___ -JJ Two 2" [51] Auxiliary Inlets ___ -JL 2 [51] Left-Hand Auxiliary Inlet ___ -JR 2 [51] Right-Hand Auxiliary Inlet ___ -M Auxiliary Foot Support (For P-Dim. 10-18 [254-457]) ___ -VL Left Hand Vent Connection | <ul style="list-style-type: none"> ___ -VP Vandal-Proof Trim ___ -X3 3 [76] Foot Extension ___ -X4 4 [102] Foot Extension ___ -29 Mechanical Test Cap Assembly (Previously Z1210-29) ___ -45 Finishing Frame for Siphon Jet System ___ -50 Flush Valve Supply Support for W.C. ___ -61 "ZZ" Coupling Wrench |
|---|--|

*REGULARLY FURNISHED UNLESS OTHERWISE SPECIFIED

REV.	DATE: 4/22/09	C.N. NO. 99924
DWG. NO. 84180	PRODUCT NO. Z1204-N-PF	

ZURN INDUSTRIES, LLC ♦ SPECIFICATION DRAINAGE OPERATION ♦ 1801 Pittsburgh Ave. ♦ Erie, PA 16514

Phone: 814/455-0921 ♦ Fax: 814/454-7929 ♦ World Wide Web: www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905/405-8272 Fax: 905/405-1292