



Z882-HDG-SW2




12" WIDE REVEAL TRENCH DRAIN SYSTEM W/ GALVANIZED STEEL FRAME AND DOUBLE SIDEWALL EXTENSIONS

SPECIFICATION SHEET

TAG _____

Design and Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SPECIFYING ENGINEER IS RESPONSIBLE FOR CONCRETE ENCASEMENT AND REINFORCING BASED UPON APPLICATION AND LOCAL CODES



NOTE: + ACTUAL CHANNEL LENGTH IS 98 3/8 [2499] TO ALLOW FOR OVERLAP

ENGINEERING SPECIFICATION: ZURN Z882-HDG-SW2

Channels shall be 96" [2438mm] long, 12" [305mm] wide reveal and have a 9-1/4" [235mm] throat. Modular channel sections shall be made of 0% water absorbent High Density Polyethylene (HDPE). Shall have a positive mechanical connection between channel sections that will not separate during the installation and shall mechanically lock into the concrete surround every 12" [305mm]. Channels shall weigh less than 5.05 lbs. [2.29kg] per linear foot, have a smooth, 3" [76mm] radiused self cleaning bottom with a Manning's coefficient of 0.009 and 1.04% or neutral 0% built in slope. Channels shall have rebar clips standard to secure trench in its final location. Shall be provided with the standard GDC grate that locks down to the frame. Zurn 12" [305mm] wide reveal Galvanized Ductile Iron Slotted Grate. Ductile Iron conforms to ASTM specification A536-84, Grade 80-55-06. Galvanized Ductile Iron grate is rated class C per the DIN EN1433 top load classifications. Supplied in 24" [608mm] nominal lengths with 13/16" [21mm] wide slots, and 1-1/2" [38mm] bearing depth. Grate has an open area of 57.50 in²/ft. [122 cm²/m]. The 1/4" [6mm] thick Galvanized Carbon Steel Frame Assembly conforms to ASTM specification A36 and Galvanizing conforms to ASTM specification A123 with 10 - 4" [102mm] long concrete anchors per 96" [2438mm]. Grate lockdown bars are to be integral to the frame. The frame is supplied with a powder coated finish. All welds must be performed by a certified welder per ASTM standard AWS D1.1. Frames Shall be produced in the U.S.A.

PREFIX OPTIONS (Check/specify appropriate options)

___-Z Eight-foot High Density Polyethylene (HDPE) Channel, Heavy-Duty Frame with Anchor Studs.*

See Additional Options on Page 2 of 2

TRENCH NO.	'A' Shallow Inv.	'B' Shallow Inv.	Flow Open Area in ² [cm ²]	Flow		
				(cfs)	(gpm)	(lps)
8202 SW2	29.25 [743]	30.25 [768]	47 [303.2]	13.79	6189	390
8203 SW2	30.25 [768]	31.25 [794]	56.2 [362.6]	14.35	6440	406
8203N SW2	31.25 [794]	31.25 [794]	56.2 [362.6]	-	-	-
8204 SW2	31.25 [794]	32.25 [819]	65.5 [422.6]	14.91	6692	422
8205 SW2	32.25 [819]	33.25 [845]	74.7 [481.9]	15.47	6943	438
8206 SW2	33.25 [845]	34.25 [870]	84 [541.9]	16.02	7190	454
8206N SW2	34.25 [870]	34.25 [870]	84 [541.9]	-	-	-
8207 SW2	34.25 [870]	35.25 [895]	93.2 [601.3]	16.58	7441	469
8208 SW2	35.25 [895]	36.25 [921]	102.5 [661.3]	17.14	7692	485
8209 SW2	36.25 [921]	37.25 [946]	111.7 [720.6]	17.69	7939	501
8209N SW2	37.25 [946]	37.25 [946]	111.7 [720.6]	-	-	-
8210 SW2	37.25 [946]	38.25 [972]	121 [780.6]	18.25	8191	517
8211 SW2	38.25 [972]	39.25 [997]	130.2 [840]	18.81	8442	533
8212 SW2	39.25 [997]	40.25 [1022]	139.5 [900]	19.36	8689	548

* Regularly furnished unless otherwise specified.

⚠ **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

⚠ **ADVERTENCIA:** Cáncer y daño reproductivo - www.P65Warnings.ca.gov

⚠ **AVERTISSEMENT:** Cancer et effets néfastes sur la reproduction - www.P65Warnings.ca.gov

Zurn Industries, LLC | Specification Drainage Operation
1801 Pittsburgh Avenue, Erie, PA 16502, Ph. 855.663.9876

In Canada | Zurn Industries Limited
7900 Goreway Drive, Unit 10, Brampton, Ontario L6T 5W6, Ph. 877.892.5216

www.zurn.com

Rev. D
Date: 07/01/25
C.N. No. 146679
Patent zurn.com/patents
Prod. | Dwg. No. Z882-HDG-SW2

Page 1 of 2



Z882-HDG-SW2

12" WIDE REVEAL TRENCH DRAIN SYSTEM W/ GALVANIZED STEEL FRAME AND DOUBLE SIDEWALL EXTENSIONS

SPECIFICATION SHEET

TAG _____

Design and Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice

SUFFIX OPTIONS (Check/specify appropriate options)

Outlet Adapters (Add/Each)

- ___-E1 Closed End Cap
- ___-E4 4 [102] No Hub End Outlet
- ___-E6 6 [152] No-Hub End Outlet
- ___-E8 8 [203] No-Hub End Outlet
- ___-U4 4 [102] No Hub Bottom Outlet
- ___-U6 6 [152] No Hub Bottom Outlet
- ___-U8 8 [203] No Hub Bottom Outlet

Grate Options (Load Classifications are per DIN EN1433)

- ___-BDC Black Acid Resistant Epoxy Coated Ductile Grate - Class C
- ___-BDE Black Acid Resistant Epoxy Coated Ductile Grate - Class E
- ___-BDF Black Acid Resistant Epoxy Coated Ductile Grate - Class F
- ___-BG Galvanized Steel Bar Grate - Class B
- ___-DC Ductile Iron Solid Cover - Class E
- ___-DGC Ductile Iron Slotted Grate - Class C
- ___-DGE Ductile Iron Slotted Grate - Class E
- ___-DGF Ductile Iron Slotted Grate - Class F
- ___-GDC Galvanized Ductile Slotted Grate - Class C*
- ___-GDE Galvanized Ductile Slotted Grate - Class E
- ___-GDF Galvanized Ductile Slotted Grate - Class F
- ___-GHPD Galvanized Heel-Proof Ductile Grate - Class B
- ___-GHPDE Galvanized Heel-Proof Ductile Slotted Grate - Class E
- ___-HPDE Heel-Proof Ductile Slotted Grate - Class E
- ___-RFGC Reinforced Slotted Galvanized Grate - Class C
- ___-RPGC Reinforced Perforated Galvanized Grate - Class C
- ___-RPGRC Reinforced Perforated Galvanized Reverse Punch Grate - Class C

Miscellaneous Options

- ___-BL High Density Polyethylene (HDPE) System with 3% Carbon Black Additive
- ___-CBF Black Acid Resistant Coated Top Frame
- ___-JC Joint Connector
- ___-VP Vandal-Proof Lockdown

MADE in the U.S.A.

- ___-ADA-USA Meets Americans with Disabilities Act Requirements - Class C
- ___-BDE-USA Black Acid Resistant Epoxy Coated Ductile Grate - Class E
- ___-DGC-USA Ductile Iron Slotted Grate - Class C
- ___-DGE-USA Ductile Iron Slotted Grate - Class E
- ___-FG Fabricated Galvanized Steel Slotted Grate - Class A
- ___-FS Fabricated Stainless Steel Slotted Grate - Class A
- ___-GADA-USA Galvanized Ductile ADA Slotted Grate - Class C
- ___-GDC-USA Galvanized Ductile Slotted Grate - Class C
- ___-GDE-USA Galvanized Ductile Slotted Grate - Class E
- ___-GHPDE-USA Galvanized Ductile Slotted Grate - Class E
- ___-HPDE-USA Heel-Proof Ductile Slotted Grate - Class E
- ___-GG Fiberglass Grate - Class A
- ___-PG Perforated Galvanized Steel Grate - Class A
- ___-PGR Galvanized Perforated Reverse Punch Anti-Slip ADA Grate - Class A
- ___-RPG Reinforced Perforated Galvanized Grate
- ___-RPGR Reinforced Galvanized Perforated Reverse Punch Anti-Slip Grate
- ___-RPS Reinforced Perforated Stainless Steel Grate
- ___-RPSR Reinforced Perforated Stainless Steel Reverse Punch Grate

MADE in the U.S.A. Miscellaneous Options

- ___-DB Bottom Dome Strainer

* Regularly furnished unless otherwise specified.

- ⚠ **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov
- ⚠ **ADVERTENCIA:** Cáncer y daño reproductivo - www.P65Warnings.ca.gov
- ⚠ **AVERTISSEMENT:** Cancer et effets néfastes sur la reproduction - www.P65Warnings.ca.gov

Zurn Industries, LLC | Specification Drainage Operation
1801 Pittsburgh Avenue, Erie, PA 16502, Ph. 855.663.9876

In Canada | Zurn Industries Limited
7900 Goreway Drive, Unit 10, Brampton, Ontario L6T 5W6, Ph. 877.892.5216

www.zurn.com

Rev.	D	Page 2 of 2
Date:	07/01/25	
C.N. No.	146679	
Patent	zurn.com/patents	
Prod. Dwg. No.	Z882-HDG-SW2	