


Z9A-E90 90° ELBOW – 1/4 Bend

Engineering Specification:

ASTM-F1412, F.R.P.P. - 210

ZURN Z9A-E90 90° ELBOW – Threaded x threaded flame-retardant polypropylene 90° elbow fitting.



Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal


Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	C	L
Z9A-E90-112	1-1/2 [38]	1-3/4 [44]	3-9/32 [83]
Z9A-E90-2	2 [51]	2-5/16 [59]	4-3/32 [104]
Z9A-E90-3	3 [76]	3 [76]	5-21/32 [144]
Z9A-E90-4	4 [102]	3-7/8 [98]	7-1/16 [179]
Z9A-E90-6	6 [152]	5 [127]	9-9/32 [236]

Z9A-E90S 90° ELBOW – Street

Engineering Specification:

ASTM-F1412, F.R.P.P. - 210

ZURN Z9A-E90S 90° ELBOW – Threaded spigot flame-retardant polypropylene 90° elbow fitting.



Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal


Model No.	Dimensions in Inches [mm]			
	Nom. Pipe Size	C	E	L
Z9A-E90S-112	1-1/2 [38]	1-3/4 [44]	2-27/32 [72]	2-13/16 [71]
Z9A-E90S-2	2 [51]	2-5/16 [59]	3-19/32 [91]	3-19/32 [91]
Z9A-E90S-3	3 [76]	3 [76]	5-1/16 [129]	5-15/16 [151]
Z9A-E90S-4	4 [102]	3-7/8 [98]	5-15/16 [151]	5-31/32 [152]
Z9A-E90S-6	6 [152]	5 [127]	5 [127]	7-5/32 [182]

Z9A-LS90 90° ELBOW – Long Sweep

Engineering Specification:

ASTM-F1412, F.R.P.P. - 210

ZURN Z9A-LS90 LONG SWEEP ELBOW – Threaded x threaded flame-retardant polypropylene 90° elbow fitting.



Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal

Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	C	L
Z9A-LS90-112*	1-1/2 [38]	3-3/16 [81]	4-23/32 [120]
Z9A-LS90-2*	2 [51]	3-27/32 [98]	5-5/8 [143]
Z9A-LS90-3	3 [76]	5-3/4 [146]	8-13/32 [214]
Z9A-LS90-4	4 [102]	6-13/16 [173]	10 [254]
Z9A-LS90-6	6 [152]	6-11/32 [161]	10-5/8 [270]

*One-piece molded.