



Z9A-YYRB COMBINATION REDUCING DOUBLE WYE and 45° ELBOW

Engineering Specification:

ZURN Z9A-YYRB COMBINATION REDUCING DOUBLE WYE and 45° ELBOW – Flame-retardant polypropylene fitting assembly.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]					
	Nom. Pipe Size	A	B	C	F	L
Z9A-YYRB-2 x 112	2 [51]	5-15/16 [135]	4-1/2 [114]	13/16 [21]	8-15/16 [227]	7-25/32 [198]
Z9A-YYRB-3 x 112	3 [76]	7-23/32 [196]	7-1/4 [184]	1-5/8 [41]	8-11/16 [221]	12-27/32 [326]
Z9A-YYRB-3 x 2	3 [76]	8-3/32 [206]	7-1/4 [184]	1-5/8 [41]	8-15/16 [227]	12-27/32 [326]
Z9A-YYRB-4 x 112	4 [102]	9-1/16 [230]	9-1/16 [230]	1-7/8 [48]	10-9/32 [261]	14-15/16 [379]
Z9A-YYRB-4 x 2	4 [102]	9-11/32 [237]	9-1/16 [230]	1-7/8 [48]	10-1/2 [267]	14-15/16 [379]
Z9A-YYRB-4 x 3	4 [102]	10-15/16 [278]	9-1/16 [230]	1-7/8 [48]	11-1/16 [281]	14-15/16 [379]
Z9A-YYRB-6 x 2	6 [152]	16-3/8 [416]	11-1/8 [283]	1-3/4 [44]	15-7/8 [403]	17-3/16 [437]
Z9A-YYRB-6 x 3	6 [152]	17-1/32 [433]	11-1/8 [283]	1-3/4 [44]	16-17/32 [419]	17-3/16 [437]
Z9A-YYRB-6 x 4	6 [152]	14-7/8 [378]	11-1/8 [283]	1-3/4 [44]	14-3/8 [365]	17-3/16 [437]


Z9A-RED REDUCING COUPLING

Engineering Specification:

ASTM-F1412, UPC®, F.R.P.P. - 210
 ZURN Z9A-RED REDUCING COUPLING – Flame-retardant polypropylene reducing fitting assembly.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]		
	Reducer Size	E	L
Z9A-RED-2 x 112	2 x 1-1/2 [51 x 38]	1-1/2 [38]	2-5/8 [67]
Z9A-RED-3 x 112	3 x 1-1/2 [76 x 38]	2-1/32 [52]	3-7/32 [82]
Z9A-RED-3 x 2	3 x 2 [76 x 51]	2-1/16 [52]	3-9/16 [90]
Z9A-RED-4 x 112	4 x 1-1/2 [102 x 38]	2-7/8 [73]	4-5/32 [106]
Z9A-RED-4 x 2	4 x 2 [102 x 51]	2-27/32 [72]	4-3/8 [111]
Z9A-RED-4 x 3	4 x 3 [102 x 76]	1-29/32 [48]	4-7/32 [107]
Z9A-RED-6 x 2	6 x 2 [152 x 51]	4-1/4 [108]	6-19/64 [160]
Z9A-RED-6 x 3	6 x 3 [152 x 76]	5-7/32 [133]	6-1/32 [153]
Z9A-RED-6 x 4	6 x 4 [152 x 102]	2-5/32 [55]	4-11/32 [110]