


Z9A-PE90S 90° STREET ELBOW – Socket x Spigot

Engineering Specification:

ASTM-F1673, UL Classified
 ZURN Z9A-PE90S 90° STREET ELBOW – Socket x spigot polyvinylidene fluoride 90° elbow fitting.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]			
	Nom. Pipe Size	C	E	L
Z9A-PE90S-112	1-1/2 [38]	1-3/4 [44]	2-27/32 [72]	2-13/16 [71]
Z9A-PE90S-2	2 [51]	2-5/16 [59]	3-19/32 [91]	3-19/32 [91]
Z9A-PE90S-3	3 [76]	3 [76]	5-1/16 [129]	5-15/16 [151]
Z9A-PE90S-4	4 [102]	3-7/8 [98]	5-15/16 [151]	5-31/32 [152]


Z9A-PLS90 PVDF LONG SWEEP 90° ELBOW

Engineering Specification:

ASTM-F1673, UL Classified
 ZURN Z9A-PLS90 LONG SWEEP ELBOW – Threaded x threaded polyvinylidene fluoride 90° elbow fitting.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	C	L
Z9A-PLS90-112*	1-1/2 [38]	3-13/16 [81]	4-23/32 [120]
Z9A-PLS90-2*	2 [51]	3-27/32 [98]	5-5/8 [143]
Z9A-PLS90-3	3 [76]	5-3/4 [146]	8-13/32 [214]
Z9A-PLS90-4	4 [102]	6-13/16 [173]	10 [254]

*One-piece molded.


Z9A-PE45 PVDF 45° ELBOW – Thread x Thread

Engineering Specification: ASTM-F1673, UL Classified

ZURN Z9A-PE45 45° ELBOW – Threaded x threaded polyvinylidene fluoride 45° elbow fitting assembly.

Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal



Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	C	L
Z9A-PE45-112	1-1/2 [38]	11/16 [17]	1-3/4 [44]
Z9A-PE45-2	2 [51]	25/32 [20]	1-27/32 [47]
Z9A-PE45-3	3 [76]	1-3/4 [44]	2-1/32 [52]
Z9A-PE45-4	4 [102]	2-13/16 [56]	4-5/16 [110]

PVDF