


Z9-PP80-NFR PIPE SCHEDULE 80

Engineering Specification:

ASTM-F1412

ZURN Z9-PP80-NFR – Schedule 80 non-flame retardant polypropylene pipe.



Note: Specify 10' or 20' lengths.


Model No.	Dimensions in Inches [mm]	
	Nom. Pipe Size	D
Z9-PP80-NFR-112	1-1/2 [38]	1-29/32 [48]
Z9-PP80-NFR-2	2 [51]	2-3/8 [60]
Z9-PP80-NFR-3	3 [76]	3-1/2 [89]
Z9-PP80-NFR-4	4 [102]	4-1/2 [114]
Z9-PP80-NFR-6	6 [152]	6-5/8 [168]

Z9A-C COUPLING

Engineering Specification:

ASTM-F1412, F.R.P.P. - 210

ZURN Z9A-C COUPLING – Flame-retardant polypropylene coupling assembly.



Options:

-F Fusion Lock; -M Mechanical Seal; -S Stab•Lock Seal

Model No.	Dimensions in Inches [mm]				
	Nom. Pipe Size	A	B	D	L
Z9A-C-112	1-1/2 [38]	5/32 [4]	1-1/16 [27]	3-1/32 [77]	2-1/4 [57]
Z9A-C-2	2 [51]	1/8 [3]	1-9/32 [33]	3-17/32 [90]	2-5/8 [67]
Z9A-C-3	3 [76]	3/16 [5]	2-3/32 [53]	5-21/64 [135]	4-3/8 [111]
Z9A-C-4	4 [102]	1/4 [6]	2-1/8 [54]	6-3/8 [162]	4-1/2 [114]
Z9A-C-6	6 [152]	9/32 [7]	2-5/32 [55]	8-19/32 [218]	4-19/32 [117]

Z9A-SC SLIP COUPLING


Engineering Specification:

ASTM-F1412, F.R.P.P. - 210

ZURN Z9A-SC SLIP COUPLING –

Flame-retardant polypropylene fitting.

For use with existing polypropylene stack.



Options:

-F Fusion Lock

Model No.	Dimensions in Inches [mm]		
	Nom. Pipe Size	D	L
Z9A-SC-112	1-1/2 [38]	3-1/32 [77]	2-1/4 [57]
Z9A-SC-2	2 [51]	3-17/32 [90]	2-5/8 [67]
Z9A-SC-3	3 [76]	5-21/64 [135]	4-3/8 [111]
Z9A-SC-4	4 [102]	6-3/8 [162]	4-1/2 [114]
Z9A-SC-6	6 [152]	8-19/32 [218]	4-19/32 [117]