

Z5562 Dual Flush 1.6/1.0 gpf, Pressure Assisted, ADA, Elongated Toilet

Z5562 EcoVantage™ Series



- Dual flush 1.6 gpf [6 Lpf] or 1.0 gpf [4 Lpf] flow rate
- High Efficiency Toilet (HET) reduces potable water usage 40%
- Vitreous china
- Pressure assist tank
- High performance EcoFlush™ technology
- Easy touch pneumatic handle actuation
- Ultra quiet flush
- Siphon jet flush action
- ADA height
- 2-1/8" fully glazed trapway
- Operating pressure range 15-125 psi
- Elongated front rim
- Chrome-plated handle
- Large water surface area
- Includes bolt caps
- Shipping Weight: 98 lbs.



Z5562 EcoVantage™ pressure assist two-piece toilet. Shown with Z5958SS-EL toilet seat (sold separately).

TOILETS

Engineering Specification

- Z5562** Vitreous china, high efficiency dual flush 1.6 gpf [6 Lpf] or 1.0 gpf [4 Lpf] pressure assisted, two-piece toilet with siphon jet bowl, elongated ADA height rim, and 12" rough-in.

Suffix Options

- RH** Tank with right-hand actuator.
Please Note: HET 1.0 gpf pressure assist tank also available. See Model Z5561.
- VL** Tank with vandal-proof locking lid.

Recommended Trim

- Z5958SS-EL** Elongated, white, closed front toilet seat with cover and stainless steel check hinge.
- Z5972-COMB** Closet bolt/wax ring kit.
- Z8800-CR** Standard stop with flexible closet riser.

Fixtures meet ASME A112.19.2 and CSA B45 standard requirements.

Fixture dimensions meet ADA/ANSI A117.1 requirements when installed per code.

See Zurn One Systems for suggested packages.

Optional Trim

- Z5975-FLO-JR** PVC Flo-Bowl Jr. closet flange kit.

ECO|VANTAGE
U.S. and Foreign Patents Pending

This Space is for Architectural/Engineering Approval