

# MODEL ZW204E - Non-Modulating Float Valve with Solenoid Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

## Required Valve Information

Quantity: \_\_\_\_\_

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Size: (Check one)  1-1/4"  1-1/2"  2"  2-1/2"  3"  4"  6"  8"  10"  12"  14"  16"

**Caution:** The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

### Function Options:

- Check all that apply
- "C" Option \* - Check Valve with Isolation Valve
  - "L" Option \* - Closing Speed Control (Standard on 8" and larger)
  - "O" Option \* - Opening Speed Control

Valve body is ductile iron, epoxy coated

### Body Options:

- Check one
- Standard - Full Port Globe Body
  - "A" Option - Angle Style Body (1-1/4" - 10")
  - "R" Option - Reduced Port Body (3" - 10" Flanged only)

### End Connections:

- Check one
- Standard - ANSI Class 150 Flanges (1-1/2" - 16")
  - "G" Option - IPS Grooved (1-1/2" - 10")
  - "TH" Option - NPT Threaded (1-1/4" - 3")
  - "Y" Option \* - ANSI Class 300 Flanges (1-1/2" - 16")

### Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
  - "V" Option \* - Viton Rubber Internals, Rated 180°F (1-1/4" - 6")
  - "Z" Option \*1 - Visual Position Indicator
  - "SO" Option \*1 - Limit Switch Open Trip
  - "SC" Option \*1 - Limit Switch Closed Trip
  - "SD" Option \*1 - Limit Switch Dual Trip

### Pilot Options:

- Check all that apply
- Standard - Isolation Valves, and "Wye" Type Strainer
  - Standard - Copper Tubing and Brass Fittings
  - "SP" Option \* - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included)
  - "SH" Option \* - Stainless Steel Braided Hoses (replaces Copper Tubing, with "VM" Option only)
  - Standard - Remotely Mounted Float
  - "VM" Option \* - Valve Mounted Float Pilot

- Check one
- Standard - 2' Standard Float Rod (Stainless Steel Rod & Float)
  - "R1" Option \* - 1' Float Rod Extension (3' total length)
  - "R2" Option \* - 2' Float Rod Extension (4' total length)
  - "R3" Option \* - 3' Float Rod Extension (5' total length)

- Must check one
- "NC" Option - Normally Closed (energize to open) Main Valve, 120vac/60 Hz Solenoid
  - "NO" Option - Normally Open (energize to close) Main Valve, 120vac/60 Hz Solenoid
  - "24NC" Option - Normally Closed (energize to open) Main Valve, 24vac/60 Hz Solenoid
  - "24NO" Option - Normally Open (energize to close) Main Valve, 24vac/60 Hz Solenoid
  - "NS" Option \* - Non-Standard Solenoid (specify Voltage/Frequency/AC/DC/Operation)  
V \_\_\_\_\_ Hz \_\_\_\_\_ AC/DC \_\_\_\_\_ NO/NC \_\_\_\_\_

- Optional
- "MO" Option \* - Manual Operator on Solenoid Valve (to control during power failure)
  - "RV" Option - Pilot Installed on Reverse Side

\*Adder to standard price applies

\*1Limit switch and position indicator options cannot be combined



DIRECTION OF FLOW ⇒  
**STANDARD - REMOTELY MOUNTED FLOAT**



DIRECTION OF FLOW ⇒  
**("VM" OPTION)**

1747 Commerce Way  
Paso Robles, CA 93446  
Phone: 855-663-9876  
Fax: 805-237-7197

Customer Service Representatives available  
Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
Fax completed forms to 805-237-7197, attention: Sales  
Call 855-663-9876, wilkinscs@zurn.com  
or visit us online at www.zurn.com

