

MODEL ZW205 - Pressure Relief / Pressure Sustaining Valve

Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

Size: (Check one) **DN32** **DN40** **DN50** **DN65** **DN80** **DN100**
 DN150 **DN200** **DN250** **DN300** **DN350** **DN400**

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.


Function Options:

- Check all that apply
- "C" Option * - Check Valve with Isolation Valve
 - "L" Option * - Closing Speed Control (Standard on DN100 or smaller)
 - "O" Option * - Opening Speed Control

Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- Standard - Full Port Globe Body
 - "A" Option - Angle Style Body (DN32 - DN250)
 - "R" Option - Reduced Port Body (DN80 - DN250 Flanged Only)



End Connections

- Options Description
- Standard - ANSI Class 150 Flanges
 - "BSD" - BS10/AS2129 Table D Flanges
 - "BSE" - BS10/AS2129 Table E Flanges
 - "BSF"* - BS10/AS2129 Table F Flanges
 - "BSH"* - BS10/AS2129 Table H Flanges
 - "G" - IPS Grooved, ANSI/AWWA C 606
 - "BG" - Grooved DN65, DN150 (76.1 mm or 165.1mm pipe OD)
 - "Y"* - ANSI Class 300 Flanges

Size Range (DN40 - DN400)

- Options Description
- "PN6" - ISO Class PN6 Flanges
 - "PN10" - ISO Class PN10 Flanges
 - "PN16" - ISO Class PN16 Flanges
 - "PN25"* - ISO Class PN25 Flanges

Size Range (DN32 - DN80)

- "TH" - NPT Threaded, ANSI/ASME B1.20.1
- "BS" - Threaded British Pipe Parallel BSPP/G size ISO
- "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO

Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 - "Z" Option *1 - Visual Position Indicator
 - "SO" Option *1 - Limit Switch Open Trip
 - "SC" Option *1 - Limit Switch Closed Trip
 - "SD" Option *1 - Limit Switch Dual Trip

Pilot Options:

- Check one
- Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer
 - Standard - Pressure Relief Pilot (340 - 1380kPa)
 - "LP3" Option* - PV-RLF Pilot (35 - 100kPa)
 - "LP2" Option* - PV-RLF Pilot (70 - 240kPa)
 - "LP" Option* - PV-RLF Pilot (205 - 620kPa)
 - "HP" Option* - PV-RLF Pilot (1000 - 2050kPa)
 - Standard - Copper Tubing and Brass Fittings
 - "SP" Option* - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing. "GL" Option included)
 - "SH" Option* - Stainless Steel Braided Hoses (only replaces Copper Tubing)
 - "RV" Option - Pilot Installed on Reverse Side
 - "GL" Option* - Liquid Filled Pressure Gauge

*Adder to standard price applies

*1Limit switch and position indicator options cannot be combined

1747 Commerce Way
 Paso Robles, CA 93446
 Phone: 855-663-9876
 Fax: 805-237-7197

Customer Service Representatives available
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST
 Fax completed forms to 805-237-7197, attention: Sales
 Call 855-663-9876, wilkinscs@zurn.com
 or visit us online at www.zurn.com

