

MODEL ZW205 - Pressure Relief / Pressure Sustaining Valve



Control Valve Order Form

Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee. Contact Customer Care for details on return policies.

Size: (Check one) 1-1/4" 1-1/2" 2" 2-1/2" 3" 4" 6" 8" 10" 12" 14" 16"

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Function Options:

- Check all that apply
- "C" Option * - Check Valve with Isolation Valve
 - "L" Option * - Closing Speed Control (Standard on 4" or smaller)
 - "O" Option * - Opening Speed Control

Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- Standard - Full Port Globe Body
 - "A" Option - Angle Style Body (1-1/4" - 10")
 - "R" Option - Reduced Port Body (3" - 10" Flanged only)

End Connections:

- Check one
- Standard - ANSI Class 150 Flanges (1-1/2" - 16")
 - "G" Option - IPS Grooved (1-1/2" - 10")
 - "TH" Option - NPT Threaded (1-1/4" - 3")
 - "Y" Option * - ANSI Class 300 Flanges (1-1/2" - 16")

Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
 - "Z" Option *¹ - Visual Position Indicator
 - "SO" Option *¹ - Limit Switch Open Trip
 - "SC" Option *¹ - Limit Switch Closed Trip
 - "SD" Option *¹ - Limit Switch Dual Trip


Pilot Options:

- Check one
- Standard - Isolation Valves, Inlet Pressure Gauge, and "Wye" Type Strainer
 - Standard - Pressure Relief Pilot (50 - 200 psi)
 - "LP3" Option - PV-RLF Pilot (5-15 psi)
 - "LP2" Option - PV-RLF Pilot (10-35 psi)
 - "LP" Option - PV-RLF Pilot (30-90 psi)
 - "HP" Option * - PV-RLF Pilot (150-300 psi)

- Check all that apply
- Standard - Copper Tubing and Brass Fittings
 - "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings & Copper Tubing. "GL" Option included)
 - "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing)

- Check all that apply
- "RV" Option - Pilot Installed on Reverse Side
 - "GL" Option * - Liquid Filled Gauge

*Adder to standard price applies ¹Limit switch and position indicator options cannot be combined



1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

