

Model ZW205FP - Fire Pump Pressure Relief Valve Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: (Check one) DN50 DN65 DN80 DN100 DN150 DN200 DN250

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Body Options:

- Check-one Standard - Full Port Globe Body
 "A" Option - Angle Style Body

Valve body is ductile iron, epoxy coated

End Connections (Check one)

- | Options | Description |
|-----------------------------------|--|
| <input type="checkbox"/> Standard | - ANSI Class 150 Flanges |
| <input type="checkbox"/> "BSD" | - BS10/AS2129 Table D Flanges |
| <input type="checkbox"/> "BSE" | - BS10/AS2129 Table E Flanges |
| <input type="checkbox"/> "BSF"* | - BS10/AS2129 Table F Flanges |
| <input type="checkbox"/> "BSH"* | - BS10/AS2129 Table H Flanges |
| <input type="checkbox"/> "G" | - IPS Grooved, ANSI/AWWA C 606 |
| <input type="checkbox"/> "BG" | - Grooved DN65, or DN150
(76.1 mm or 165.1mm pipe OD) |
| <input type="checkbox"/> "Y"* | - ANSI Class 300 Flanges |

Size Range (DN50 - DN250)

- | Options | Description |
|----------------------------------|--------------------------|
| <input type="checkbox"/> "PN6" | - ISO Class PN6 Flanges |
| <input type="checkbox"/> "PN10" | - ISO Class PN10 Flanges |
| <input type="checkbox"/> "PN16" | - ISO Class PN16 Flanges |
| <input type="checkbox"/> "PN25"* | - ISO Class PN25 Flanges |



DIRECTION OF FLOW ⇒

ISO

Size Range (DN50 - DN80)

- | | |
|-------------------------------|--|
| <input type="checkbox"/> "TH" | - NPT Threaded, ANSI/ASME B1.20.1 |
| <input type="checkbox"/> "BS" | - Threaded British Pipe Parallel BSPP/G size ISO |
| <input type="checkbox"/> "BT" | - Threaded British Pipe Tapered BSPT/Rc size |

Main Valve Options:

- Optional: Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 Check "Z" Option * - Visual Position Indicator (Not available with SP pilot)
 Z or Z2 "Z2" Option * - Stainless Steel Dry Position Indicator

Pilot Options:

- Standard - 3-Way Gauge Isolation Valve on Inlet Pressure Gauge (UL), and "Wye" Type Strainer

- | | | |
|-----------|--|---------------------------------|
| Check one | <input type="checkbox"/> Standard | - PV-RLF Pilot (340 - 1380kPa) |
| | <input type="checkbox"/> "HP" Option * | - PV-RLF Pilot (1000 - 2050kPa) |

- | | | |
|-----------|--|--|
| Check one | <input type="checkbox"/> Standard | - Copper Tubing and Brass Fittings |
| | <input type="checkbox"/> "SP" Option * | - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing) |

- Optional "RV" Option - Pilot on Reverse Side



DIRECTION OF FLOW ⇒

UL & ULC Listed, FM® Approved

***Adder to standard price applies**

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

