

Model ZW205FP - Fire Pump Pressure Relief Valve Control Valve Order Form



Customer:	Date:
Contact:	Email:
Telephone/Fax:	Ref. P. O.

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: 2" (DN50) 2-1/2" (DN65) 3" (DN80) 4" (DN100) 6" (DN150) 8" (DN200) 10" (DN250)
(Check one)

Caution: The recommended installation orientation for ACVs is horizontal, with the valve cover up. 6" and larger valves should only be installed horizontally, with the valve cover up, due to the difficulty of properly bleeding air out of the cover and performing maintenance on valves installed in the vertical orientation.

Body Options:

Check one Standard - Full Port Globe Body
 "A" Option - Angle Style Body

Valve body is ductile iron, epoxy coated

End Connections (Check one)

Size Range 2" - 10" (DN50 - DN250)

Options Description
 Standard - ANSI Class 150 Flanges
 "BSD" - BS10/AS2129 Table D Flanges
 "BSE" - BS10/AS2129 Table E Flanges
 "BSF"* - BS10/AS2129 Table F Flanges
 "BSH"* - BS10/AS2129 Table H Flanges
 "G" - IPS Grooved, ANSI/AWWA C 606
 "BG" - Grooved 2-1/2", or 6"
 (76.1 mm or 165.1mm pipe OD)
 "Y"* - ANSI Class 300 Flanges

Options Description
 "PN6" - ISO Class PN6 Flanges
 "PN10" - ISO Class PN10 Flanges
 "PN16" - ISO Class PN16 Flanges
 "PN25"* - ISO Class PN25 Flanges

Size Range (2" - 3", DN50 - DN80)

"TH" - NPT Threaded, ANSI/ASME B1.20.1
 "BS" - Threaded British Pipe Parallel BSPP/G size ISO
 "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO



Main Valve Options:

Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
 Optional: "Z" Option * - Visual Position Indicator (Not available with SP pilot)
 Check "Z2" Option * - Stainless Steel Dry Position Indicator
 Z OR Z2

Pilot Options:

Standard - 3-Way Gauge Isolation Valve on Inlet Pressure Gauge (UL), and "Wye" Type Strainer

Check one Standard - PV-RLF Pilot (50 - 200 psi) (340 - 1380kPa)
 "HP" Option * - PV-RLF Pilot (150 - 300 psi) (1000 - 2050kPa)

Check one Standard - Copper Tubing and Brass Fittings
 "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)

Optional "RV" Option - Pilot on Reverse Side



UL & ULC Listed, FM® Approved

*Adder to standard price applies

1747 Commerce Way
 Paso Robles, CA 93446
 Phone: 855-663-9876
 Fax: 805-237-7197

Customer Service Representatives available
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST
 Fax completed forms to 805-237-7197, attention: Sales
 Call 855-663-9876, wilkinscs@zurn.com
 or visit us online at www.zurn.com

