

Model ZW205FP - Fire Pump Pressure Relief Valve Control Valve Order Form



Customer: _____ **Date:** _____

Contact: _____ **Email:** _____

Telephone/Fax: _____ **Ref. P. O.:** _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: 2" (DN50) 2-1/2" (DN65) 3" (DN80) 4" (DN100) 6" (DN150) 8" (DN200) 10" (DN250)
(Check one)

Body Options:

Check one Standard - Full Port Globe Body
 "A" Option - Angle Style Body


Valve body is ductile iron, epoxy coated

End Connections (Check one)

Size Range 2" - 10" (DN50 - DN250)

Options	Description
<input type="checkbox"/> Standard	ANSI Class 150 Flanges
<input type="checkbox"/> "BSD"	BS10/AS2129 Table D Flanges
<input type="checkbox"/> "BSE"	BS10/AS2129 Table E Flanges
<input type="checkbox"/> "BSF"*	BS10/AS2129 Table F Flanges
<input type="checkbox"/> "BSH"*	BS10/AS2129 Table H Flanges
<input type="checkbox"/> "G"	IPS Grooved, ANSI/AWWA C 606
<input type="checkbox"/> "BG"	Grooved 2-1/2", or 6" (76.1 mm or 165.1mm pipe OD)
<input type="checkbox"/> "Y"*	ANSI Class 300 Flanges

Options	Description
<input type="checkbox"/> "PN6"	ISO Class PN6 Flanges
<input type="checkbox"/> "PN10"	ISO Class PN10 Flanges
<input type="checkbox"/> "PN16"	ISO Class PN16 Flanges
<input type="checkbox"/> "PN25"*	ISO Class PN25 Flanges



Size Range (2" - 3", DN50 - DN80)

<input type="checkbox"/> "TH"	NPT Threaded, ANSI/ASME B1.20.1
<input type="checkbox"/> "BS"	Threaded British Pipe Parallel BSPP/G size ISO
<input type="checkbox"/> "BT"	Threaded British Pipe Tapered BSPT/Rc size ISO

Main Valve Options:

Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide
Optional "Z" Option * - Visual Position Indicator

Pilot Options:

Standard - 3-Way Gauge Isolation Valve on Inlet Pressure Gauge (UL), and "Wye" Type Strainer

Check one <input type="checkbox"/> Standard	PV-RLF Pilot (50 - 200 psi) (340 - 1380kPa)
<input type="checkbox"/> "HP" Option *	PV-RLF Pilot (150 - 300 psi) (1000 - 2050kPa)

Check one <input type="checkbox"/> Standard	Copper Tubing and Brass Fittings
<input type="checkbox"/> "SP" Option *	All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)

Optional "RV" Option - Pilot on Reverse Side



UL & ULC Listed, FM® Approved

*Adder to standard price applies

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurn.com
or visit us online at www.zurn.com

