

# Model ZW205FP - Fire Pump Pressure Relief Valve Control Valve Order Form



Customer: \_\_\_\_\_ Date: \_\_\_\_\_  
 Contact: \_\_\_\_\_ Email: \_\_\_\_\_  
 Telephone/Fax: \_\_\_\_\_ Ref. P. O. \_\_\_\_\_

## Required Valve Information

Quantity: \_\_\_\_\_

All returns are subject to a restocking/refurbishing fee.  
 Contact Customer Care for details on return policies.

Size: (Check one)     2"     2-1/2"     3"     4"     6"     8"     10"

### Function Options:

"C" Option\* - 40XL2 Hydraulic Check

### Body Options:

Check one  Standard - Full Port Globe Body  
 "A" Option - Angle Style Body

Valve body is ductile iron, epoxy coated

### End Connections:

Check one  Standard - ANSI Class 150 Flanges (2" - 10")  
 "G" Option - IPS Grooved (2" - 10")  
 "TH" Option - NPT Threaded (2" - 3")  
 "Y" Option\* - ANSI Class 300 Flanges (2" - 10")



DIRECTION OF FLOW ⇒

### Main Valve Options:

Standard - Stainless Steel Seat, Seal Ring Retainer, and Stem Guide  
 Optional  "Z" Option\* - Visual Position Indicator

### Pilot Options:

Standard - 3-Way Gauge Isolation Valve on Inlet Pressure Gauge(UL), and "Wye" Type Strainer

Check one  Standard - PV-RLF Pilot (50 - 200 psi)  
 "HP" Option\* - PV-RLF Pilot (150 - 300 psi)

Check one  Standard - Copper Tubing and Brass Fittings  
 "SP" Option\* - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve & Copper Tubing)

Optional  "RV" Option - Pilot on Reverse Side



DIRECTION OF FLOW ⇒

**UL & ULC Listed, FM® Approve**

\*Adder to standard price applies

1747 Commerce Way  
 Paso Robles, CA 93446  
 Phone: 855-663-9876  
 Fax: 805-237-7197

Customer Service Representatives available  
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST  
 Fax completed forms to 805-237-7197, attention: Sales  
 Call 855-663-9876, wilkinscs@zurn.com  
 or visit us online at www.zurn.com

