

MODEL ZW209 - Pressure Reducing Valve Control Valve Order Form



Customer: _____ Date: _____

Contact: _____ Email: _____

Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: (Check one) DN32 DN40 DN50 DN65 DN80 DN100
 DN150 DN200 DN250 DN300 DN350 DN400

Function Options:

- Check all that apply
- "C" Option * - Check Valve with Isolation Valve
 - "L" Option * - Closing Speed Control
 - "O" Option * - Opening Speed Control (Standard on DN100 or smaller)

Valve body is ductile iron, epoxy coated

Body Options:

- Check one
- Standard - Full Port Globe Body
 - "A" Option - Angle Style Body (DN32 - DN250)
 - "R" Option - Reduced Port Body (DN80 - DN250 Flanged Only)



DIRECTION OF FLOW ⇒

End Connections (Check one) Size Range (DN40 - DN400)

- | Options | Description | Options | Description |
|-----------------------------------|---|----------------------------------|--------------------------|
| <input type="checkbox"/> Standard | - ANSI Class 150 Flanges | <input type="checkbox"/> "PN6" | - ISO Class PN6 Flanges |
| <input type="checkbox"/> "BSD" | - BS10/AS2129 Table D Flanges | <input type="checkbox"/> "PN10" | - ISO Class PN10 Flanges |
| <input type="checkbox"/> "BSE" | - BS10/AS2129 Table E Flanges | <input type="checkbox"/> "PN16" | - ISO Class PN16 Flanges |
| <input type="checkbox"/> "BSF"* | - BS10/AS2129 Table F Flanges | <input type="checkbox"/> "PN25"* | - ISO Class PN25 Flanges |
| <input type="checkbox"/> "BSH"* | - BS10/AS2129 Table H Flanges | | |
| <input type="checkbox"/> "G" | - IPS Grooved, ANSI/AWWA C 606 | | |
| <input type="checkbox"/> "BG" | - Grooved DN65, or DN150 (76.1 mm or 165.1mm pipe OD) | | |
| <input type="checkbox"/> "Y"* | - ANSI Class 300 Flanges | | |

Size Range (DN32 - DN80)

- "TH" - NPT Threaded, ANSI/ASME B1.20.1
- "BS" - Threaded British Pipe Parallel BSPP/G size ISO
- "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO

Main Valve Options:

- Check all that apply
- Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
 - "V" Option * - Viton Rubber Internals, Rated 82°C (DN32 - DN150 only available with "LP" or "HP" Option)
 - "Z" Option * - Visual Position Indicator

Pilot Options:

- Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer

- Check one
- Standard - PRXL Pilot (100 - 1000kPa)
 - "LP" Option * - PV-PRD Pilot (35 - 170kPa)
 - "HP" Option * - PV-PRD Pilot (205 - 2050kPa)

- Check all that apply
- Standard - Copper Tubing and Brass Fittings
 - "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve and Copper Tubing. "GL" Option included)
 - "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing)

- Check all that apply
- "RV" Option - Pilot Installed on Reverse Side
 - "GL" Option * - Liquid Filled Pressure Gauge

*Adder to standard price applies

1747 Commerce Way
Paso Robles, CA 93446
Phone: 855-663-9876
Fax: 805-237-7197

Customer Service Representatives available
Monday through Friday 5:30 a.m. to 5:00 p.m., PST
Fax completed forms to 805-237-7197, attention: Sales
Call 855-663-9876, wilkinscs@zurnwilkins.com
or visit us online at www.zurn.com

