

MODEL ZW209 - Pressure Reducing Valve Control Valve Order Form



Customer: _____ Date: _____

Contact: _____ Email: _____

Telephone/Fax: _____ Ref. P. O. _____

Required Valve Information

Quantity: _____

All returns are subject to a restocking/refurbishing fee.
Contact Customer Care for details on return policies.

Size: 1-1/4" (DN32) 1-1/2" (DN40) 2" (DN50) 2-1/2" (DN65) 3" (DN80) 4" (DN100)
 Check one 6" (DN150) 8" (DN200) 10" (DN250) 12" (DN300) 14" (DN350) 16" (DN400)

Function Options:

Check all that apply "C" Option * - Check Valve with Isolation Valve
 "L" Option * - Closing Speed Control
 "O" Option * - Opening Speed Control (Standard on 4" or smaller)

Valve body is ductile iron, epoxy coated

Body Options:

Check one Standard - Full Port Globe Body
 "A" Option - Angle Style Body (1-1/4" (DN32) - 10" (DN250))
 "R" Option - Reduced Port Body (3" (DN80) - 10" (DN250) Flanged Only)

End Connections (Check one) Size Range (1-1/2" - 16", DN40 - DN400)

Options	Description	Options	Description
<input type="checkbox"/> Standard	- ANSI Class 150 Flanges	<input type="checkbox"/> "PN6"	- ISO Class PN6 Flanges
<input type="checkbox"/> "BSD"	- BS10/AS2129 Table D Flanges	<input type="checkbox"/> "PN10"	- ISO Class PN10 Flanges
<input type="checkbox"/> "BSE"	- BS10/AS2129 Table E Flanges	<input type="checkbox"/> "PN16"	- ISO Class PN16 Flanges
<input type="checkbox"/> "BSF"*	- BS10/AS2129 Table F Flanges	<input type="checkbox"/> "PN25"*	- ISO Class PN25 Flanges
<input type="checkbox"/> "BSH"*	- BS10/AS2129 Table H Flanges		
<input type="checkbox"/> "G"	- IPS Grooved, ANSI/AWWA C 606		
<input type="checkbox"/> "BG"	- Grooved 2-1/2", or 6" (76.1 mm or 165.1mm pipe OD)		
<input type="checkbox"/> "Y"*	- ANSI Class 300 Flanges		



Size Range (1-1/4" - 3", DN32 - DN80)

"TH" - NPT Threaded, ANSI/ASME B1.20.1
 "BS" - Threaded British Pipe Parallel BSPP/G size ISO
 "BT" - Threaded British Pipe Tapered BSPT/Rc size ISO

Main Valve Options:

Check all that apply Standard - Stainless Steel Seat, Seal Ring Retainer and Stem Guide
 "V" Option * - Viton Rubber Internals, Rated 180°F, 82°C (1-1/4" - 6", DN32 - DN150 only available with "LP" or "HP" Option)
 "Z" Option * - Visual Position Indicator

Pilot Options:

Standard - Isolation Valves, Inlet and Outlet Pressure Gauges, and "Wye" Type Strainer

Check one Standard - PRXL Pilot (15 - 150 psi, 100 - 1000kPa)
 "LP" Option * - PV-PRD Pilot (5 - 25 psi, 35 - 170kPa)
 "HP" Option * - PV-PRD Pilot (30 - 300 psi, 205 - 2050kPa)

Check all that apply Standard - Copper Tubing and Brass Fittings
 "SP" Option * - All Stainless Steel Pilotry (replaces all Brass Fittings, Pilot Valve and Copper Tubing. "GL" Option included)
 "SH" Option * - Stainless Steel Braided Hoses (only replaces Copper Tubing)

Check all that apply "RV" Option - Pilot Installed on Reverse Side
 "GL" Option * - Liquid Filled Pressure Gauge

*Adder to standard price applies

1747 Commerce Way
 Paso Robles, CA 93446
 Phone: 855-663-9876
 Fax: 805-237-7197

Customer Service Representatives available
 Monday through Friday 5:30 a.m. to 5:00 p.m., PST
 Fax completed forms to 805-237-7197, attention: Sales
 Call 855-663-9876, wilkinscs@zurn.com
 or visit us online at www.zurn.com

