



Spec•Com Specified Commercial | Industrial Systems

Zurn Specified Commercial Systems offer drainage solutions for commercial and industrial applications. Specified Commercial drainage systems are used in applications where heavier loading may occur, such as commercial kitchens, warehouses, and industrial plants that encounter fork lift, hand cart and other heavy traffic loading.

Features and Benefits:

- Pre-sloped trench drain systems are offered in high density polyethylene, stainless steel, and fiberglass with Class A, pedestrian and ADA compliant through Class F 200,000 lb. load rating grate options to meet your job site needs.
- Z874 systems offer 4-corner grate lock down for dynamic loading situations.
- Save labor costs up to 75% with mechanical interlocking connections for fast installation.
- Install high volume drainage faster with the Hi-Cap® Slotted Drainage System's lightweight sections – for driveway access and loading dock areas.
- Systems are available from 4" to 21" pre-sloped with radiused bottom.
- System provides containment of hazardous spills.
- Utility trench systems offer dual containment, sub-surface utility passageways while providing surface accessibility for maintenance.




Kitchens and Restaurants
Plants
Site Drainage
Warehouses

1.855.ONE.ZURN
www.zurn.com

Trench Drains

Stainless Steel

Z890 5' Length
Pre-Sloped, Stainless Steel




Z895 5' Length
Pre-Sloped, Stainless Steel




HDPE


Z886 80" Length
Pre-Sloped, HDPE




Z874-12 80" Length
Pre-Sloped, HDPE




Z886-FGF 80" Length,
Pre-Sloped with Class F Frame & Grate




Z874-18 80" Length
Pre-Sloped, HDPE



Z882 8' Length
Pre-Sloped, HDPE




Z874-21 80" Length
Pre-Sloped, HDPE




Fiberglass

Z806 10' Length
Pre-Sloped, Fiberglass



Z812 10' Length
Pre-Sloped, Fiberglass



Fabrications

Custom fabrications are available upon request for all Zurn Linear Trench systems.


Forklift rated available.

Frame and grate systems also available for Cast-In-Place applications.




Slot Drains


Z888-4 40" Length, Non-Sloped
Available with 4" extension and heavy-duty frame




Z888-6 40" Length, Non-Sloped
Available with 4" extension and heavy-duty frame




Z888-8 40" Length, Non-Sloped
Available with 4" extension and heavy-duty frame



Z891 5' Length, Pre-Sloped
Stainless Steel




Z888-12 80" Length
Also available Z888-18 and -36



Catch Basins


Z887 24" x 24" Catch Basin
Available in 6" x 20" and 12" x 24"



Utility Trench – Special Duty

Z874-U-HD

Available medium-duty systems with aluminum frames and covers, or steel covers.



Grate	Dimensions in Inches			
	A Throat Width	B Max. Depth	C Grate Width	D Grate Height
Z874-U-4-HD	4 [102]	22 [559]	6 [152]	3/4 [19]
Z874-U-9-HD	9 [229]	22 [559]	12 [305]	1-1/4 [32]
Z874-U-12-HD	12 [305]	30 [762]	17 [432]	1-3/4 [44]
Z874-U-18-HD	18 [457]	30 [762]	23 [584]	1-3/4 [44]
Z874-U-19-HD	19 [483]	30 [762]	24 [610]	1-3/4 [44]
Z874-U-21-HD	21 [533]	30 [762]	27 [686]	1-3/4 [44]

The Z874-U is a neutral, non-sloped utility drain system. Depths of this system may range from 4" to 30".

Z885 Oil Separator



Z885 Dimensional Data

Capacity Gallons	Top Dimension	Height Inches [mm]	Approx. Wt. Lbs. [Kg]
	Inches [mm]		
140	70-1/2 x 35-1/4 [1791 x 895]	30 [762]	328 [149]
200	70-1/2 x 35-1/4 [1791 x 895]	36 [914]	354 [161]
260	70-1/2 x 35-1/4 [1791 x 895]	48 [1219]	382 [173]