

ZURN

LABORATORY FAUCET - DOUBLE

Z826F3-XL


TAG _____



Engineering Specifications: Zurn AquaSpec® Z826F3-XL

Polished chrome-plated double laboratory faucet with integral shank, quarter turn ceramic disc cartridges and a 6" [152mm] cast brass swing spout. Unit is furnished with a 2.2 GPM [8.3 L] aerator (complying with ANSI A112.18.1 Standard for flow), 2" [51mm] vandal-resistant color-coded metal dome lever handles, mounting hardware and stainless steel flex connection hoses.

Zurn Lead Compliant* "XL" products are a line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with state laws and local codes that mandate lead content levels. Zurn "XL" products are manufactured with *not more than 0.25% lead content when used with respect to wetted surfaces of pipes and pipe fittings, plumbing fitting and fixtures: California Health & Safety Code § 116875; Vermont 9 VCA § 2470h



Note: All dimensions are for reference only. Do not use for pre-plumbing.

OPTIONAL ACCESSORIES

Suffix	Description
—AR	Anti-Rotation Pins
—CST	Copper Supply Tubes
—G	1-1/4" [32mm] Grid Strainer Drain
—HCT	Hot/Cold Text Indexes
—MY	Mixing Yoke Assembly Instead Of Copper Supplies
—PT	1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend
—2F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator
—3F	0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
—4F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Laminar Flow Outlet
—7F	1.0 GPM [3.8L] Pressure Compensating Female Spray Outlet
—16F	1.0 GPM [3.8L] Vandal-Resistant Pressure Compensating Female Spray Outlet
—17F	1.5 GPM [5.7L] Vandal-Resistant Pressure Compensating Female Aerator
—18F	1.5 GPM [5.7L] Vandal-Resistant Pressure Compensating Female Laminar Flow Outlet
—18FH	18" [457mm] S.S. Braided Flex Hoses
—19F	1.5 GPM [5.7 L] Anti-Microbial Pressure Compensating Female Laminar Flow Outlet
—21F	1.0 GPM [3.8L] Pressure Compensating Female Laminar Flow Outlet
—22F	1.0 GPM [3.8L] Pressure Compensating Vandal-Resistant Female Laminar Flow Outlet
—23F	1.5 GPM [5.7L] Pressure Compensating Female Aerator

ZURN INDUSTRIES, LLC ♦ COMMERCIAL BRASS OPERATION ♦ 2640 SOUTH WORK STREET ♦ FALCONER NY 14733

Phone: 1-800-997-3876 ♦ Fax: 1-919-775-3541 ♦ www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905/405-8272 Fax: 905/405-1292