

# Z6000AV-2

AquaVantage<sup>®</sup> 'AV' Exposed Water Closet Flush Valve





# Flow Options

-ONE*	1.1 gpf High Efficiency Flush
-HET*	1.28 gpf High Efficiency Flush
-WS1	1.6 gpf Low Consumption Flush
-WS	3.5 gpf


### Accessories

□ -BG	BioCare Handle
🗆 -DF	Dual Flush Handle
🗆 -Н	Handle on Front of Flush Valve
🗆 -HL	1" [25] Metal Push Button on Front
□ -HL3	3" [76] Metal Push Button on Front
□-YH	One Wall Bumper
□-YJ	Split Ring Pipe Support
□-YK	Solid Ring Pipe Support
🗆 -YL	Solid Ring Pipe Support with Bumper
□	Other



\*This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

ZURN INDUSTRIES, LLC. COMMERCIAL BRASS OPERATION 5900 ELWIN BUCHANAN DRIVE SANFORD NC 27330 PHONE: 1-800-997-3876 FAX: 919-775-3541 WWW.ZURN.COM IN CANADA: ZURN INDUSTRIES LIMITED 7900 GOREWAY DRIVE UNIT 10 BRAMPTON, ONTARIO L6T5W6 PHONE: 905-405-8272 FAX: 905-405-1292



# **ENGINEERING SPECIFICATIONS**

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior.

- Zurn's AquaVantage® TPE diaphragm Clog Resistant Triple filtered by-pass Chloramine resistant Dual seal
- Proprietary DR resistant low lead brass alloy
- > Handle
  - ADA compliant Non-hold open and no leak feature
- Control Stop

Internal siphon-guard protection Vandal resistant stop cap Sweat solder kit Cast wall flange with set screw

Vacuum Breaker High back pressure

One piece hex coupling nut

- Internal seals
  - Chloramine resistant
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

#### Architectural/Engineering Approval

The information contained in this document is subject to change without notice.

AquaVantage® is a registered trademark of Zurn Industries, LLC.