

Note: All dimensions are for reference only. Do not use for pre-plumbing

OPTIONAL ACCESSORIES

| Suffix | Description |
|----------|---|
| FC | 2.0 GPM [7.6 L] Laminar Flow Control in Base of Spout |
| PT | 1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend |
| WM | Wall Mount |
| 2F | 2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator |
| 2F 3F | 0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Spray Outlet |
| 4F | 2.2 GPM [8.3 L]Vandal-Resistant Pressure Compensating Female Laminar Flow |
| 7F | 1.0 GPM [3.8 L] Pressure Compensating Female Spray Outlet |
| 16F | 1.0 GPM [3.8 L] Vandal-Resistant Pressure Compensating Female Spray Outlet |
| -17F | 1.5 GPM [5.7 L] Vandal-Resistant Pressure Compensating Female Aerator |
| 18F | 1.5 GPM [5.7 L] Vandal-Resistant Pressure Compensating Female Laminar Flow |
| 19F | 1.5 GPM [5.7 L] Anti-Microbial Pressure Compensating Female Laminar Flow Outlet |
| 21F | 1.0 GPM [3.8L] Female Laminar Flow Outlet |
| 22F | 1.0 GPM [3.8L] Vandal-Resistant Female Laminar Flow Outlet |
| -23F | 1.5 GPM [5.7L] Pressure Compensating Female Aerator |

Phone: 1-800-997-3876 ♦ Fax: 1-919-775-3541 ♦ www.zurn.com In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905/405-8272 Fax: 905/405-1292